



NexxaCore Technical Datasheet – The Summit Collection

Plank Size & Packing	9" Width x 72" Length 17.67 sf/box, 4 pcs/bx, 36 lbs/box 56 bxs/pallet; 2060 lbs/pallet		
Overall Thickness	10mm		
Bevel & Texture	Accented Bevels™ w/ EIR Technology		
Wear Layer	Guardia G3™ – 28 Mil light commercial wearlayer (0.7mm) Ultra Scratch-resistant Anti-microbial		
LVT Layer	1.5mm PVC		
Core	7mm Nexxacore™ waterproof core with zero wood fibers		
Underlayment	attached 1.5mm Silencio XPE™ closed cell, impact/ acoustic		
Locking System	Unilin Uniclic Angle/Tap		
Installation	Floating		
Warranty	Lifetime Limited Residential Wear Warranty Lifetime Limited Structural Warranty Lifetime Limited Waterproof Warranty 10 Year Limited Medium Commercial Warranty		
Compliance	Assure Certified Floorscore Indoor Air Quality Certified		
Test Data	Static Load	ASTM F-970	Pass
	Dimensional stability	ASTM F2199	Pass
	Fire Rating	ASTM E648	Class 1
	Slip resistance	ASTM C1028	Pass
	Phthalates	CPSC-CH-C1001	Not Detectable
	IIC	ASTM E492	55 dB no drop ceiling, 150mm slab
	ΔIIC	ASTM E2179	22 dB no drop ceiling, 150mm slab
	STC	ASTM E90	53 dB no drop ceiling, 150mm slab