



TECHNICAL PRODUCT SPECIFICATIONS
FOR CUSHION VINYL FLOORING

THOROUGHFARE

SPECIFICATIONS:

PRODUCT NAME:	THOROUGHFARE
CONSTRUCTION	RESILIENT CUSHION VINYL
THICKNESS	60 MILS
WEAR LAYER	15 MILS
TOTAL WEIGHT	1.9LBS. PER SQ. YD
STANDARD WIDTH	15'6"
GLOSS LEVEL	MATTE
AVERAGE LENGTH	125 FT.
ASTM E-648 CRITICAL RADIANT FLUX	CLASS 1
ASTM F2199-02	≤ 0,40%
ASTM C1028-96 STATIC COEFFICIENT OF FRICTION	0.66
ASTM F1303-04	TYPE 1, GRADE 3, CLASS C
ASTM F 137-03	PASSES 6MM MANDREL
EN ISO 105 BO2 LIGHT STABILITY	≥6
EN12667 UNDERFLOOR HEATING	SUITABLE

INSTALLATION:

END USE:	RECREATIONAL VEHICLE, MANUFACTURED HOUSING
INSTALLATION:	LOOSE LAY AND PERIMETER STAPLE. RADIANT FLOOR HEAT COMPATIBLE TO 80°F

ADDITIONAL INFO:

WEAR WARRANTY	7 YEARS
---------------	---------

MANUFACTURING TOLERANCES:

Slight distortion and/or waviness in the product when unwinding it from a roll is inherent to PVC resilient flooring, which expands and contracts based upon the ambient storage conditions. These distortions will relax out after unwinding the product or can be stretched out during installation with reasonable manual force. If the distortions are larger than 2 inch height and do not stretch/relax out this product is likely to have permanent deformations which should be reported back to the manufacturer.

We strive to manufacture and deliver the highest quality possible for our customers. In order to consistently provide our customers with a standard roll size we may allow up to four minor defects to pass through our quality assurance program to maintain the standard roll size. The minor imperfections are noticeably marked with red tape or “flags” to assist our customers with achieving the highest yield from each roll.