



REPOSADO®

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 178 mm x 1220 mm
Overall Thickness*	0.08" / 2.0 mm (nom)
Wear Layer	8 mil / 0.20 mm featuring Tuff Shield® finish
Edge	Square
Standard Colors	8 colors
Installation Method	Glue-Down
Wear Limited Warranty	20-Years Residential / 10-Years Light Commercial
Recycled Content	This product does not contain recycled content.
Packaging	51.34 ft² (4.77 m²) per carton 22 pieces per carton 60 cartons per pallet
Weight Per Carton	37.70 lbs / 17.10 kg



Sunrise RPS-302

Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648	Class I, CRF ≥0.91
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed
STC Sound Testing	ASTM E 90 / E 413	61
IIC Sound Testing	ASTM E 492 / E 989	64



BETTER I WEAR LIMITED WARRANTY



Paloma RPS-301



Barrel RPS-305



Sunrise RPS-302




Casa RPS-306




Matador RPS-303



Agave RPS-307



Siesta RPS-304



Spirit RPS-308

*All measurements are nominal. Sound Testing will vary depending on the specific floor/ ceiling assembly.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images.

Please visit www.earthwerks.com for full warranty details & installation guidelines. All specifications & offerings are subject to change without notice.