







REPOSADO® PRO

Classification ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile

Size* 7" x 48"(nom)

Overall Thickness* 2.5 mm

Wear Layer 20 mil featuring **auff Shield** finish


Edge Square
Standard Colors 8 colors
Installation Method Glue-Down

Wear Limited Warranty Lifetime Residential / 30-Year Light Commercial Recycled Content This product does not contain recycled content.

Packaging 41.98 ft² (3.90 m²) per carton

18 pieces per carton 60 cartons per pallet

Weight Per Carton 38.42 lbs / 17.43 kg



















Product Testing

Chemical Resistance ASTM F 925 Passed

Critical Radiant Flux ASTM E 648 Class I, CRF ≥0.45

ASTM F 2199 Passed Dimensional Stability ASTM F 137 Flexibility Passed **ASTM F 1514** Passed Resistance to Heat ASTM F 1515 Passed Resistance to Light ASTM E 662 Passed Smoke Density ASTM F 970 Static Load Limit Passed Thickness ASTM F 386 Passed

 STC Sound Testing
 ASTM E 90 / E 413
 51

 IIC Sound Testing
 ASTM E 492 / E 989
 71



Paloma RPR-521



Sunrise RPR-522



Matador RPR-523



Siesta RPR-524



Barrel RPR-525



Casa RPR-526



Agave RPR-527



Spirit RPR-528

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images.

Please visit www.earthwerks.com for full warranty details & installation guidelines. All specifications & offerings are subject to change without notice.

EarthWerks®

^{*}All measurements are nominal. Sound Testing will vary depending on the specific floor/ ceiling assembly.