



CHASSIS®

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 177.80 mm x 1219.20 mm
Overall Thickness*	0.08" / 2.0 mm (nom)
Wear Layer	6 mil / 0.15 mm featuring Tuff Shield® finish
Edge	Square
Standard Colors	8 colors
Installation Method	Glue-Down
Wear Limited Warranty	20-Year Residential / 10-Year Light Commercial
Recycled Content	This product contains recycled content.
Packaging	32.72 ft² (3.04 m²) per carton 14 pieces per carton 85 cartons per pallet
Weight Per Carton	25.57 lbs / 11.60 kg



Product Testing


Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648	Class I, ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed
STC	ASTM E 492	61
IIC	ASTM E 989	64



BETTER | WEAR LIMITED WARRANTY



CERTIFIED BY
SCS Global Services



Axle CHA 7475



Clutch CHA 7476




Spitfire CHA 7477 (Heavy Shade Variation)



Backbone CHA 7478 (Heavy Shade Variation)




Caspas CHA 7479



Armature CHA 7480 (Heavy Shade Variation)



Motorcoach CHA 7481



Suspension CHA 7482

*All measurements are nominal. Sound Testing will vary depending on the specific floor/ ceiling assembly.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images.

Please visit www.earthwerks.com for full warranty details & installation guidelines. All specifications & offerings are subject to change without notice.