



AVENUES II

TECHNICAL PRODUCT SPECIFICATIONS CUSHION VINYL SHEET

SPECIFICATIONS:

STYLE NAME	AVENUES II
FINISH	NATURQUEST- ENHANCED EMBOSS TECHNOLOGY/ PU LACQUER
PATTERN REPEAT	REFER TO DESIGN CHART BELOW
NOMINAL WEAR LAYER THICKNESS	10 MILS (0.25 MM)
NOMINAL PRODUCT THICKNESS	75 GAUGE (1.9 MM)
BACKING TYPE	POWERBAC
AVAILABLE WIDTH	12'
STANDARD ROLL LENGTH	131 FT.
WEIGHT PER SQUARE YARD	2.525 LBS/SQ. YD.
COUNTRY OF ORIGIN	MANUFACTURED IN USA OF GLOBAL COMPONENTS

PERFORMANCE:

ASTM F1303 TYPE 1 GRADE 3 CLASS C	AATCC 134 (STEP) ELECTROSTATIC 0.8 K.V. OR LOWER
FLOORSCORE CERTIFIED	ASTM C1028 SCOF- DRY .73 WET.66
CPSC-CH-C1001-09.3 PHTHALATES - MEETS CPSIA GUIDE	ASTM F970 STATIC LOAD - PASSES
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F137 FLEXIBILITY - PASSES 6 MM MANDREL
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F963 HEAVY METAL CONTENT ANALYSIS - PASSES	ASTM D4060 ABRASION RESISTANCE - 22,000 CYCLES
WATER PENETRATION IMPACT - 10,000 CYCLES - PASSES	100% RECLAIMABLE

INSTALLATION:

END USE	RESIDENTIAL
INSTALLATION METHOD	DIRECT GLUE DOWN/LOOSE LAY UP TO 25 SQ YD/225 SQ FT
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
INSTALLATION SUNDRIES AS REQUIRED:	BEAUFLO 4N1 MULTIPURPOSE ADHESIVE, BEAUFLO HS RESILIENT SPRAY, BEAUFLO ISOLATE, BEAUFLO MOISTURE SEAL 95, BEAUFLO SUBSTRATE PRIMER, BEAUFLO CV SEAM SEALER.

WARRANTIES:

15 YEAR LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY
--

DESIGN CHART:

COLLECTION	COLOR NAME	SKU NUMBER	PATTERN REPEAT
AVENUES II	NAPOLEON AVE	AM-AV2-097M	39.37" x 39.37
AVENUES II	ESPLANADE AVE	AM-AV2-730M	39.37" x 39.37
AVENUES II	CARROLLTON AVE	AM-AV2-617M	39.37" x 59.10"
AVENUES II	CLAIBORNE AVE	AM-AV2-694M	39.37" x 59.10"
AVENUES II	ELYSIAN FIELDS	AM-AV2-720M	39.37" x 59.10"

CARE & MAINTENANCE:

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand. For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop.