



## DELTA

Classification ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile  
Size\* 7" x 48" / 177.8 mm x 1219.2 mm (Plank)

Overall Thickness\* 0.08" / 2.0 mm  
Wear Layer 6 mil / 0.15 mm, featuring **Tuff Shield** finish  
Edge Square  
Standard Colors 3 standard planks  
Installation Method Glue Down  
Wear Limited Warranty 20 Year Residential / 10-Year Light Commercial  
Recycled Content This product contains 50% recycled content.  
100% recyclable post-use

Packaging **PLANK**  
32.72 ft<sup>2</sup> (3.04 m<sup>2</sup>) per carton  
14 pieces per carton  
85 cartons per pallet

Weight Per Carton 25.57 lbs / 11.60 kg

### Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF $\geq 0.45$
Dimensional Stability	ASTM F 2199	Passed
+STC Sound Testing	ASTM E 492-09	+STC 61
+IIC Sound Testing	ASTM E 989-06	+IIC 64
Flexability	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed

