









## CHASSIS™ ADVANTAGE Plank and Tile

ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile Classification

7" x 48" / 177.8 mm x 1219.2 mm (Plank) Size\*

18" x 18" / 457.2 mm x 457.2 mm (Tile)

Overall Thickness\* 0.08" / 2.0 mm

Wear Layer 12 mil / 0.30 mm, featuring **auff Shielo** finish

Edge

Standard Colors 6 standard planks / 2 standard tiles

Installation Method Glue Down

Wear Limited Warranty 30 Year Residential / 20-Year Light Commercial This product contains 50% recycled content. Recycled Content

100% recyclable post-use

**PLANK** Packaging

32.72 ft<sup>2</sup> (3.04 m<sup>2</sup>) per carton 14 pieces per carton

85 cartons per pallet 17 pallets per 20' container

Weight Per Carton 25.57 lbs / 11.60 kg

35.95 ft<sup>2</sup> (3.34 m<sup>2</sup>) per carton 16 pieces per carton 76 cartons per pallet 17 pallets per 20' container

27.62 lbs / 12.53 kg









**OSCS**certified









Chemical Resistance ASTM F 925 Passed Critical Radiant Flux ASTM E 648-06 Class I, CRF ≥0.45 Dimensional Stability **ASTM F 2199** Passed +STC Sound Testing ASTM E 492-09 +STC 61 +IIC 64 +IIC Sound Testing ASTM E 989-06 Flexability ASTM F 137 Passed Resistance to Heat **ASTM F 1514** Passed Resistance to Light ASTM F 1515 Passed Smoke Density ASTM E 662-06 Passed

Static Load Limit Thickness

**ASTM F 970** Passed ASTM F 386 Passed

Caspas CAD 8919



Armature CAD 8920 - Heavy Shade Variation



Motorcoach CAD 8921



Veridian CAD 8925









Armature CAD-7480 (Heavy Shade Variation)







30 Year Residential / 20 Year Light Commercial Wear Limited Warranty



Suspension CAD 8922



Farnham CAD 8923



Shepherd CAD 8924



Calais CAD 8926

<sup>\*</sup>All measurements are nominal. +Sound Testing will vary depending on the specific floor/ ceiling assembly. Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.