



# CHASSIS™ PRO Plank and Tile

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile	
Size*	7" x 48" / 177.8 mm x 1219.2 mm (Plank) 18" x 18" / 457.2 mm x 457.2 mm (Tile)	
Overall Thickness*	0.12" / 3.0 mm	
Wear Layer	20 mil / 0.50 mm, featuring <b>tuff Shield</b> finish	
Edge	Square	
Standard Colors	6 standard planks / 2 standard tiles	
Installation Method	Glue Down	
Wear Limited Warranty	Lifetime Residential / 30-Year Commercial	
Recycled Content	This product contains 50% recycled content. 100% recyclable post-use	
Packaging	<b>PLANK</b> 27.98 ft <sup>2</sup> (2.60 m <sup>2</sup> ) per carton 12 pieces per carton 65 cartons per pallet 17 pallets per 20' container	<b>TILE</b> 22.49 ft <sup>2</sup> (2.09m <sup>2</sup> ) per carton 10 pieces per carton 80 cartons per pallet 17 pallets per 20' container
Weight Per Carton	31.97 lbs / 14.50 kg	26.64 lbs / 12.08 kg



Armature CPR-9260 (Heavy Shade Variation)

## Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
+STC Sound Testing	ASTM E 492-09	+STC 61
+IIC Sound Testing	ASTM E 989-06	+IIC 67
Flexability	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed




**PREMIUM**  
Lifetime Residential / 30 Year  
Commercial Wear Limited Warranty

SCS Certified




Caspas CPR 9259




Suspension CPR 9262



Armature CPR 9260 - Heavy Shade Variation



Farnham CPR 9263



Motorcoach CPR 9261



Shepherd CPR 9264



Veridian CPR 9265



Calais CPR 9266

\*All measurements are nominal. +Sound Testing will vary depending on the specific floor/ ceiling assembly.

Please visit [www.earthwerks.com](http://www.earthwerks.com) for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.