



PARKHILL® PLUS PARKHILL® EIR PLUS

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 177.8mm x 1219.2mm
Overall Thickness*	0.25" / 7mm (6mm + 1mm cushion backing)
Wearlayer	20 mil / 0.50mm, featuring tuff Shield finish
Edge	Micro Beveled
Standard Colors	4 standard planks / 8 EIR planks
Installation Method	Click Floating Floor
Wear Limited Warranty	Lifetime Residential / 30-Year Commercial
Recycled Content	This product contains no recycled content. 100% recyclable post-use
Packaging	23.64 ft ² (2.20 m ²) per carton 10 pieces per carton 60 cartons per pallet 17 pallets per 20' container
Weight Per Carton	37.51 lbs / 17 kg



Parkhill® EIR Plus - PKH 348

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.91
Dimensional Stability	ASTM F 2199	Passed
*STC Sound Testing	ASTM E 492-09	*STC 60
*IIC Sound Testing	ASTM E 989-06	*IIC 70
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed




SCS Certified



Sawmill PKH 342 CB (Non EIR)



CrossTimber PKH 343 CB (Non EIR)



DryWash PKH 344 CB (Non EIR)



Bespoke PKH 346 CB (Non EIR)



Copperbrooke PKH 347 CB



Stafford PKH 348 CB




Junction PKH 350 CB



Grove Park PKH 351 CB



White Fang PKH 381 CB NEW



Otter PKH 382 CB NEW



Brown Bear PKH 383 CB NEW



Wild Hare PKH 384 CB NEW



*Sound Testing will vary depending on the specific floor/ ceiling assembly.

Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.