




PAVILION™ PLUS Plank

Classification	ASTM F 1700-18A Class III, type A or B Solid Vinyl Floor Tile
Size*	6" x 36" / 152.4 mm x 914.4 mm
Overall Thickness*	0.14" / 3.5 mm (2.5 mm LVP + 1 mm cushion backing)
Wearlayer	8 mil / 0.20 mm, featuring Scuff Shield finish
Backing	1 mm cushion backing
Edge	Square
Standard Colors	8 standard planks
Installation Method	Glue Down
Wear Limited Warranty	20-Year Residential / 10-Year Light Commercial
Recycled Content	This product contains recycled content. 100% recyclable post-use
Packaging	21 ft ² (1.95 m ²) per carton 14 pieces per carton 78 cartons per pallet 20 pallets per 20' container
Weight Per Carton	23.15 lbs / 10.50 kg




Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-19	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-19	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed
+IIC Sound Testing	ASTM E 989-19	+IIC 67




Tenement SCP 681 CB **(IN STOCK)**




Tower Block SCP 682 CB *(Special Order)*



Maisonette SCP 683 CB **(IN STOCK)**




Regency SCP 686 CB *(Special Order)*




Midtown SCP 684 CB **(IN STOCK)**



Elevation SCP 687 CB *(Special Order)*



Park Place SCP 685 CB **(IN STOCK)**



Townhouse SCP 688 CB *(Special Order)*

*All measurements are nominal. +Sound Testing will vary depending on the specific floor/ ceiling assembly.
Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.