



SHERBROOKE® PLUS

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 177.8mm x 1219.2mm
Overall Thickness*	0.22" / 6.5mm (5.5mm + 1mm cushion backing)
Wearlayer	12 mil / 0.30mm, featuring Tuff Shield finish
Edge	Micro Beveled
Standard Colors	12 standard planks
Installation Method	Click Floating Floor
Wear Limited Warranty	30-Year Residential / 20-Year Light Commercial
Recycled Content	This product contains no recycled content. 100% recyclable post-use
Packaging	23.64 ft ² (2.20 m ²) per carton 10 pieces per carton 65 cartons per pallet 17 pallets per 20' container
Weight Per Carton	34.86 lbs / 15.80 kg



Sherbrooke® Plus - SHB 2168 CB

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.91
Dimensional Stability	ASTM F 2199	Passed
*STC Sound Testing	ASTM E 492-09	*STC 61
*IIC Sound Testing	ASTM E 989-06	*IIC 71
Flexability	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



Jackson Pine SHB 2167 CB NEW



Saddle SHB 2168 CB NEW



Burlap SHB 2169 CB NEW



Linen SHB 2170 CB NEW



Natural SHB 2171 CB



Chestnut SHB 2172 CB



Newport SHB 2173 CB



Esperanza SHB 2174 CB



Mineral SHB 2176 CB



Township SHB 2179 CB



Gristmill SHB 2180 CB



Brompton SHB 2182 CB

*Sound Testing will vary depending on the specific floor/ ceiling assembly.

Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.