




# TAVERN™ PLUS

Classification	ASTM F-3261-17 Resilient flooring in modular format with Rigid Polymeric Core
Size*	7" x 48" / 180 mm x 1220 mm
Overall Thickness*	0.20" / 5.0 mm
Wear Layer	12 mil / 0.30 mm featuring <b>Tuff Shield</b> finish
Edge	Micro Beveled
Standard Colors	6 standard colors
Installation Method	Click Floating Floor
Backing	1 mm Cushion Backing
Wear Limited Warranty	30-Year Residential / 20-Year Light Commercial
Recycled Content	This product contains no recycled content. 100 % recyclable post use.
Packaging	18.91 ft <sup>2</sup> (1.76 m <sup>2</sup> ) per carton 8 pieces per carton 65 cartons per pallet 18 pallets per 20' container
Weight Per Carton	32.25 lbs / 14.63 kg



Dubbel - TVN 506 CB


Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-17	Class I, CRF ≥ 0.92
Dimensional Stability	ISO 23999	Passed
Residual Indentation	ASTM F 1914	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-15A	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 387	Passed
STC Sound Testing	ASTM E 413-16	STC 62
IIC Sound Testing	ASTM E 989-06	IIC 71



Pale Ale TVN 501 CB




Dunkel TVN 504 CB



Pilsner TVN 502 CB



Imperial TVN 505 CB



Pint TVN 503 CB



Dubbel TVN 506 CB

\* Products within this collection may feature a high degree of shade variation from plank to plank.

\*All measurements are nominal. + Sound Testing will vary depending on the specific floor/ceiling assembly. Please visit [www.earthwerks.com](http://www.earthwerks.com) for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.