



DEVAN™ Plank

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	6" x 36" / 152.40 mm x 914.40 mm
Overall Thickness*	0.08" / 2.0 mm
Wearlayer	8 mil / 0.20 mm - featuring Tuff Shield finish
Edge	Square
Standard Colors	4 standard planks
Installation Method	Glue Down
Wear Limited Warranty	20-Year Residential / 10-Year Light Commercial
Recycled Content	This product contains recycled content. 100% recyclable post-use
Packaging	27 ft ² (2.51 m ²) per carton 18 pieces per carton 108 cartons per pallet 18 pallets per 20' container
Weight Per Carton	21.56 lbs / 9.78 kg



Torrance-EVN 541 TS

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
+STC Sound Testing	ASTM E 492-09	+STC 61
+IIC Sound Testing	ASTM E 989-06	+IIC 64
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



BETTER
20 Year Residential / 10 Year Light
Commercial Wear Limited Warranty



SCS certified



Torrance EVN 541 TS



Graze EVN 543 TS



Cricket EVN 542 TS



Harbour EVN 544 TS

*All measurements are nominal. +Sound Testing will vary depending on the specific floor/ ceiling assembly.

Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.