

AMAZONIA

MA (MATTE)
GLAZED PORCELAIN TILES



eliane

AMAZONIA
GLAZED PORCELAIN TILES

Finish
MA (Matte)

Amazonia Amendoa



19.5x91.2 cm | 8"x36"
MA (MATTE)

Amazonia Canela



19.5x91.2 cm | 8"x36"
MA (MATTE)

Amazonia Oliva



19.5x91.2 cm | 8"x36"
MA (MATTE)



WALLS



FLOORS



EXTERIOR



WATER
PROOF



FIRE
PROOF

AMAZONIA

GLAZED PORCELAIN TILES

SIZES

	Product	Finish	Rect.	Work Size	Thick	Faces	Sq. Ft./ Carton	Pieces/ Carton	
	Wall/Floor 8"x 36"	Amazonia	Matte	No	195 x 912 mm 7-11/16" x 35-15/16"	9 mm	17	11.52	6

USAGE RECOMMENDATION

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Exterior Walls Applications	N/A	✓
Interior Walls/Backsplashes	N/A	✓
Interior Countertops	N/A	✓
Facades	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3.

NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION AND CARE

Grout Joint Recommendation 1/8"

Shade Variation V3 - MODERATE VARIATION

Professional tile installation is recommended. For complete installation instructions consult the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.

Eliane's recommendation for flooring care: sweep or vacuum the surface. Then mop the floor using a mop with water and a neutral cleaner (soap less) or a general household cleaner. Follow it with a clean water rinsed mop and wipe dry the floor to prevent film formation. For wall tiles care, Eliane recommends using a cloth with water and a neutral cleaner (soap less) or a general household cleaner.

QUALITY WARRANTY



Standard quality tiles manufactured by Eliane Ceramic Tiles meet or exceed ISO 13006, NBR 15463 and NBR 13818, ANSI A137.1 standards.



Eliane Porcelain Tiles are certified, ANSI/ASTM compliant, ≤ 0.5% water absorption.



Eliane ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC).



Eliane ceramic and porcelain tiles are NOT flammable, except mesh material of mesh mounted mosaics.

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	≤ 0.5%
Breaking Strength	C648	≥ 275 lbs
DCOF WET	ANSI A137.1 ANSI A326.3	≥0.42
Surface Abrasion (PEI)	C1027	3
Frost Resistance	C1026	Yes
Scratch Hardness	MOHS	9
Chemical Resistance	C650	Resistant



eliane

BOLICK DISTRIBUTORS

2055 N. Airway Dr. Baton
Rouge, LA 70815

225-927-8016

www.bolickdistributors.com

