

KEYSTONE

AC (SATIN)
GLAZED PORCELAIN TILES



eliane



KEYSTONE

GLAZED PORCELAIN TILES

Keystone Nero



30x60 cm | 12"x24"
AC (SATIN)

Keystone Gray



30x60 cm | 12"x24"
AC (SATIN)


Keystone White



30x60 cm | 12"x24"
AC (SATIN)


Finish
AC (Satin)

Keystone Hex Nero



20x23 cm | 8"x9"
AC (SATIN)

Keystone Hex Gray



20x23 cm | 8"x9"
AC (SATIN)

Keystone Hex White



20x23 cm | 8"x9"
AC (SATIN)







KEYSTONE

GLAZED PORCELAIN TILES

SIZES

Product	Finish	Rect.	Work Size	Thick	Sq. Ft./ Thick	Pieces/ Faces Carton	Pieces/ Carton
 Wall/Floor 12"x 24" Keystone AC	Satin	No	302.3 x 601.2 mm 11-7/8" x 23-5/8"	7.5 mm	18	17.60	9
 Wall/Floor Hex 8"x 9" Keystone Hex AC	Satin	No	200.4 x 231.6 mm 7-7/8" x 9-1/8"	8.0 mm	20	9.37	25

USAGE RECOMMENDATION

	Target DCOF wet	Suitable
Dry & Level – Interior Floor (Residential / Light Commercial)	N/A	✓
Wet & Level – Interior Floor (Residential / Light Commercial)	≥ 0.42	✓
Shower Floors (Residential / Light Commercial)	≥ 0.42	✓
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Exterior Walls Applications	N/A	✓
Interior Walls/Backsplashes	N/A	✓
Interior Countertops	N/A	✓
Facades	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3.

Note: Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	≤ 0.5%
Breaking Strength	C648	≥ 275 lbs
DCOF WET	ANSI A137.1 ANSI A326.3	≥0.42
Frost Resistance	C1026	Yes
Surface Abrasion (PEI)	C1027	3 - 4
Scratch Hardness	MOHS	8
Chemical Resistance	C650	Resistant

INSTALLATION AND CARE

Grout Joint Recommendation 1/8"
Shade Variation  V2 - SLIGHT VARIATION

Professional tile installation is recommended. For complete installation instructions consult the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.

Eliane's recommendation for flooring care: sweep or vacuum the surface. Then mop the floor using a mop with water and a neutral cleaner (soap less) or a general household cleaner. Follow it with a clean water rinsed mop and wipe dry the floor to prevent film formation. For wall tiles care, Eliane recommends using a cloth with water and a neutral cleaner (soap less) or a general household cleaner.

QUALITY WARRANTY

QUALITY Standard quality tiles manufactured by Eliane Ceramic Tiles meet or exceed ISO 13006, NBR 15463 and NBR 13818, ANSI A137.1 standards.

FIRE PROOF Eliane ceramic and porcelain tiles are NOT flammable, except mesh material of mesh mounted mosaics.

VOC FREE Eliane ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC).

RECYCLED Recycled content:
Pre-consumer Porc. 12x24 : 44.4%
Porc. Hex : 31.4%
Post-consumer Porc. 12x24 : 0 %
Porc. Hex : 8.0 %

Porcelain tiles on this series are:





eliane

BOLICK DISTRIBUTORS

2055 N. Airway Dr. Baton
Rouge, LA 70815

225-927-8016

www.bolickdistributors.com

