



NexxaCore Technical Datasheet – The Masterpiece Collection

| | | | |
|----------------------|--|---------------|----------------|
| Plank Size & Packing | 9" Width (228mm) x 71" Length (1800mm) 17.67 sf/box, 4 pc/bx, 52 lbs/bx 48 bxs/pallet; 2550 lbs/pallet | | |
| Overall Thickness | 8mm | | |
| Bevel & Texture | Accented Bevels™ w/ Embossed-In-Registration(EIR) | | |
| Wear Layer | Guardia G3 20 Mil commercial wearlayer Ultra Scraach-resistant Anti-Microbial | | |
| Core | 6.5mm extruded Rigid Nexxacore™ (2 to 1 limestone to vinyl ratio) | | |
| Underlayment | 1.5mm Silencio XPE™ closed cell, acoustical underlayment | | |
| Locking System | Valinge 5G Angle / Fold w/ tab | | |
| Installation | Floating | | |
| Warranty | Lifetime Limited Residential Wear Warranty Lifetime Limited Structural Warranty Lifetime Limited Waterproof Warranty 10 Year Limited Medium Commercial Warranty | | |
| Compliance | CA Carb Compliant Floorscore Certified Assure Certified | | |
| Test Data | Static Load | ASTM F-970 | Pass |
| | Dimensional stability | ASTM F2199 | Pass |
| | Fire Rating | ASTM E648 | Class 1 |
| | IIC | ASTM E492 | 54 dB |
| | ΔIIC | ASTM E2179 | 20 |
| | STC | ASTM E90 | 53 dB |
| | Slip resistance | ASTM C1028 | Pass |
| | Phthalates | CPSC-CH-C1001 | Not Detectable |