

7 1/4" x 48" Planks Dimensions 12" x 24" Tiles Thickness 7.5 mm with 1 mm high density padattached Pad Type IXPE 20 mil Wear Layer 32.62 Planks Sq. Ft. / Box 27.99 Tiles **Box Weight** 46 Lbs/Box Tiles 52 Lbs/Box Planks Commercial 10 Year Limited Medium Residential Limited Lifetime Warranty **Moisture Warranty** Limited Lifetime Structure Warranty Limited Lifetime Construction **Engineered Vinyl** Composite Float or Glue Down Installation Method Finish **UV-Cured** Installation Grade Above, On and Below **Locking Method** Valinge **Edge Profile** Micro Bevel

Spec and Test Info Tiles





Planks





ASTM-E 648	Critical Radiant Flux	Meets or Exceeds, Class 1
ASTM E 492-09	Impact Sound Conduction	IIC 59 db
ASTM 90-09	Airborne Sound Conduction	STC 61 db
ASTM C 518	Thermal Resistance	R Value – 0.57
NALFA 3.2	Thickness Swell	Class 4, Heavy Commercial
NALFA 3.3	Xenon Light Resistance	Class 4, Heavy Commercial
NALFA 3.4	Cleanability-Stain Resistance	Class 4, Heavy Commercial
NALFA 3.5	Large Ball Impact Resistance	Class 4, Heavy Commercial
NALFA 3.6	Small Ball Impact Resistance	Class 4, Heavy Commercial
NALFA 3.8	Dimensional Tolerance	Class 4, Heavy Commercial
NALFA 3.9	Caster Chair	Class 3, Commercial
NALFA 3.10	Surface Bonding	1.31N/mm – Exceeds Class 3 Commercial Requirement
ASTM C 1028-96	Static Coefficient of Friction	0.68 (Slip Resistance) Passes ADA/OSHA Standard
ASTM F 970-07	Static Load Limit	0.004 inch – Passes at 250 psi
ASTM F 2753	Rolling Load Over Resilient FC	0.024 inch
ASTM F 1514	Color Resistance to Heat	Meets <8.0 Delta E Requirement
ASTM F 1515	Color Resistance to Light	Meets <8.0 Delta E Requirement

<u>Certifications:</u> Carb Compliant, Contributes to LEED Credits, California 01350 Compliant, GREENGUARD GOLD Certified, Phthalates Free



