

## **IMAGINE FIGURATIVE**

## Residential Broadloom

Broadloom

Construction

Tufted, Cut Pile

**Broadloom Width** 

13'6" (4.11 m)

**Pattern Repeat** 

Varies with pattern

**Face Fiber** 

100% STAINMASTER® Tactesse® Nylon Type 6,6

Yarn Finish

Superba® Heatset

Stain Resist / Soil Release

LotusFX® Fiber Shield

**Dye Method** 

Millitron®

**Tufted Face Weight** 

 $40 \text{ oz/yd}^2 (1,356 \text{ g/m}^2)$ 

Gauge

1/10 (39.4/10 cm)

**Stitches** 

15/in (59.1/10 cm)

**Tufts** 

150/in<sup>2</sup> (2,328.5/100 cm<sup>2</sup>)

**Finished Pile Height** 

0.30" (7.62 mm)

**Average Density (Finished)** 

6,000

**Standard Backing** 

Endura-Loc™

**Nominal Total Thickness** 

0.38" (9.65 mm)

**Nominal Total Weight** 

 $73 \text{ oz/yd}^2 (2,475 \text{ g/m}^2)$ 

Flammability (Radiant Panel ASTM-E- 648)

≥ 0.45 (Class I)

**Recommended Traffic** 

Residential

**Recommended Maintenance** 

Capture® Carpet and Fabric Care

Indoor Air Quality—CRI Green Label Plus™

GLP2860, Carpet Category 1Y

## LIMITED LIFETIME WARRANTIES

All Food and Beverage Stains
Pet Urine Stains
Soil Resistance
Anti-Static

## ADDITIONAL LIMITED WARRANTIES

25-Year Abrasive Wear25-Year Texture Retention2-Year Latent Manufacturing Defects



