

IMAGINE FIGURATIVE

Design for Business™

Broadloom

Construction

Tufted, Cut Pile

Broadloom Width

13'6" (4.11 m)

Pattern Repeat

Varies with pattern

Face Fiber

100% STAINMASTER® Nylon Type 6,6

Yarn Finish

Superba® Heatset

Stain Resist / Soil Release

LotusFX® Fiber Shield

Dye Method

Millitron®

Tufted Face Weight

 $30 \text{ oz/yd}^2 (1,017.2 \text{ g/m}^2)$

Gauge

1/10 (39.4/10 cm)

Stitches

12/in (47.2/10 cm)

Tufts

120/in² (1,859.7/100 cm²)

Finished Pile Height

0.26" (6.6 mm)

Average Density (Finished)

5,143

Standard Backing

Endura-Loc™

Nominal Total Thickness

0.34" (8.64 mm)

Nominal Total Weight

 $63 \text{ oz/yd}^2 (2,136.2 \text{ g/m}^2)$

Flammability (Radiant Panel ASTM-E- 648) \geq

0.45 (Class I)

Texture Appearance Retention Rating (TARR)

Heavy Traffic End-Use Applications

Recommended Maintenance

Capture® Carpet and Fabric Care

Indoor Air Quality—CRI Green Label Plus™

GLP2860, Carpet Category 1Y

LIMITED LIFETIME WARRANTIES

All Food and Beverage Stains
Pet Urine Stains
Soil Resistance
Anti-Static

ADDITIONAL LIMITED WARRANTIES

25-Year Abrasive Wear25-Year Texture Retention2-Year Latent Manufacturing Defects



