



Accord Colors

Indicates Bolick Stock

(6) Accord Colors 4' Coved Lengths 4" WALL BASE TYPE TP RUBBER

The Accord System offers 36 color choices that span the entire spectrum of premium rubber flooring products, including wall base, tiles, stair treads and finishing accessories.

Custom colors available for a minimum.

					
Almond 403	Off White 244	Beach Sand 030	Light Gray 208	Frosted Jade 210	Mocha 597
					
Cream 205	Baja 519	Sky Gray 663	Carmine Gray 674	Daffodil 820	Mango 070
					
Desert Sand 118	Gray Beige 209	Jackalope 190	Ash 603	Sugar Snap 055	Geranium 966
					
Ginger 503	Sandy Tan 112	Gray 204	Gray Blue 672	Mountain Meadow 077	Peacock 120
					
Tumbleweed 033	Clay 527	Moonbeam 050	Rocky 660	Dark Forest 331	Ocean Blue 115
					
Pecan 504	Brown 502	BlackBrown 523	Charcoal 217	Black 701	Navy 875

BurkeBase®

Style	BurkeBase Type TP 1/8" ** (Non-Ortho Phthalate)
Construction	Thermoplastic Rubber
Finish	Matte
Classification	ASTM F1861 Type TP, Group 1
Total Thickness	1/8" (3.2 mm)
Profile	Coved or Toeless 2.5" (64 mm) 4" (102 mm) 4.5" (114 mm) 6" (152 mm)
Colors	100 (36 are Accord)
Packaging	1-100' continuous roll or 25-4' pieces
Weight Per Carton – 2.5" / 4" / 4.5" / 6" / 10"	Coved = 25/38/41/53 lbs. Toeless = 24/35/41/52 lbs.
Weight Per Carton – Corners	Coved = 3/4/9 lbs. Coved = 3/4/9 lbs.
Corners (must be ordered at time of wall base order to ensure color match)	Factory pre-formed corners available
Adhesive	MR-101
Testing	
Static Load (ASTM E970)	500 psi
Flooring Radiant Panel (ASTM E648)	Passes - Class I; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - < 450
Environmental Data	
Indoor Air Quality	FloorScore Certified
LEED Scoreboard	May contribute to LEED and Green Globes credits LEED 2009: MRc5 Regional Material; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEEDv4: IEQc2 - Low Emitting Materials
Manufacturing	Calhoun, GA and Eustis, FL (USA)
Warranty	
	Limited 5-Year Commercial Warranty

- Maintain a minimum temperature in the spaces to receive the wall base and accessories of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed. Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.

* Type TS Coved 4' lengths available in 4" and 6".

** Type TP & TV Coved and Toeless 4' lengths & 100' rolls available in 2.5", 4", 4.5", and 6" heights.

Products Available with Accord Colors



Color Anchor Rubber Tile



Stair Treads and Nosings



Wall Base

For more information, contact your Bolick representative.