



Mangrove Oak VE75MANO




Sandal Oak VE75SANO



Seashell Oak VE75SEAO




Marina Oak VE75MARO



Maritime Walnut VE75MARW



Pearl Oak VE75PEAO




Sandbar Hickory VE75SANH




White Cap Oak VE75WHIO




Dune Oak VE75DUNO



Pier Oak VE75PIEO



Wharf Oak VE75WHAO



Hampton Hickory VE75HAMH



Features

- Dimensions: 7½" x 6'2" RL
- Thickness: 1/2" Engineered TrueCore Centerply
2mm Slice Cut Face
- Finish: Nu Oil® (Oak)
TrueMark® Glaze Tek Poly (Walnut, Hickory)
- Edge Detail: Handcrafted Microbevel
- Surface Texture: Wire Brushed
- Certified: TSCA Title IV Compliant - Clean air
Certified Renewable Sourcing
- TrueCore: Third Party Certified veneer
- Warranty: Limited Lifetime residential finish
Limited Lifetime residential structural
3 year commercial finish (Nu Oil®)
5 year commercial finish (Glaze Tek)
10 year commercial structural
- Maintenance: Clean with NuOil® Floor Cleaner (Oak)
Clean with TrueClean Floor Cleaner (Walnut & Hickory)
For full care and maintenance instructions visit
HallmarkFloors.com/Floor-Care-Maintenance

Benefits





- Finish: Protective low sheen - provides a truly natural wood floor (Oak)
Guaranteed quality and durability - long lasting finish
100% Renewable with Hallmark's Restoration Oil (Oak)
100% renewable without sanding via a Screen & Recoat (Walnut & Hickory)
- Wear Layer: Wear layer provides lasting durability
Easier to repair or touch up if an accident occurs
- Structure: 75% Greater dimensional stability than 3/4" solid
Healthy indoor air quality - Third party certified
TrueCore centerply for maximum stability



Trim Options

- Stair Nose
- T-molding
- Threshold
- Reducer

Installation

-  Nail Down
-  Glue Down
-  Float
-  Over Radiant Heat
(Excluding Hickory)

Installs over: concrete, wood, vinyl floors and radiant heat systems. Above, on or below grade. See complete installation instructions. Hallmark Hickory and Solid products are not approved for installation over Radiant Heat.

Fumed Characteristics

What to Expect with Fumed Floors



1. Regional Variation
2. Batch Variation
3. Plank Variation

Mangrove Oak, Sandal Oak, Seashell Oak, Marina Oak, Pearl Oak are Fumed.

Fuming simply deepens the natural colors and highlights the contrast of the wood planks without using stain to cover them. Our process creates a naturally richer, darker, clearer floor with a higher contrast of colors from board to board.

What is Fumed Hardwood?

This is a natural accelerated aging process used to enhance the dark to light shades within every wood plank, batch & region. The deepening in color and variation is created by adding a natural oxidizing agent in a controlled environment to react with the naturally present tannins in the wood – Time, Temperature & Tannins (naturally present in the wood) mix to create one of a kind planks that we add to our Collections. While a very controlled environment and process, it is not 100% precise, every region, grove and tree produces individually unique high contrast color palette.

Learn more about the beauty of fuming,
www.hallmarkfloors.com/the-beauty-of-fumed-hardwood-floors/

Light Characteristics

Wood Floor Plank with Natural Finish
Light* Exposure Over 48 Months

New Installation			
12 Months Later	24 Months Later	48 Months Later	*All band widths

Wood Characteristics

Color, Graining & Natural Changes



Wood flooring is a natural product that will feature distinct color and graining between planks. Each board contains large to small knots, sap wood, and a high contrast within the natural and lighter stained visuals. Knots and voids may or may not be filled with dark putty.

Note: This sample may not be representative of your entire installed floor, for your reference and the latest updated information, please refer to hallmarkfloors.com to see our online room scenes and product galleries.

Before installation review the samples with the floor and verify our beautiful one of a kind floor is what you are expecting.

Installation constitutes acceptance.