



## REPOSADO® PLUS

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" (nom)
Overall Thickness*	3.5 mm (2.5 mm + 1 mm cushion backing)
Wear Layer	12 mil / 0.30 mm featuring <b>Tuff Shield</b> finish
Edge	Square
Standard Colors	8 colors
Installation Method	Glue-Down
Wear Limited Warranty	30-Year Residential / 20-Year Light Commercial
Recycled Content	This product does not contain recycled content.
Packaging	32.67 ft² (3.04 m²) per carton 14 pieces per carton 60 cartons per pallet
Weight Per Carton	34.87 lbs / 15.82 kg



Sunrise RPD-732CB

### Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed
STC Sound Testing	ASTM E 90 / E 413	62
IIC Sound Testing	ASTM E 492 / E 989	72



BEST I WEAR LIMITED WARRANTY



Paloma RPD-731CB




Barrel RPD-735CB



Sunrise RPD-732CB




Casa RPD-736CB




Matador RPD-733CB



Agave RPD-737CB



Siesta RPD-734CB



Spirit RPD-738CB

\*All measurements are nominal. Sound Testing will vary depending on the specific floor/ ceiling assembly.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images.

Please visit [www.earthwerks.com](http://www.earthwerks.com) for full warranty details & installation guidelines. All specifications & offerings are subject to change without notice.