



## STRATOSPHERE™

|                       |  |
|-----------------------|--|
| Classification        | ASTM F-3261 Resilient flooring in modular format with Solid Polymeric Core     |
| Size*                 | 7" x 60" / 177.8 mm x 1524 mm  |
| Overall Thickness*    | 0.22" / 5.5 mm (4.5 mm + 1 mm cushion backing) (nom)                           |
| Wear Layer            | 20 mil / 0.50 mm featuring <b>Tuff Shield</b> finish                           |
| Edge                  | Bevel  |
| Standard Colors       | 6 colors   |
| Installation Method   | Angle / Angle  |
| Wear Limited Warranty | Lifetime Residential   |
| Recycled Content      | This product contains recycled content.  |
| Packaging             | 23.62 ft² (2.19 m²) per carton<br>8 pieces per carton<br>50 cartons per pallet |
| Weight Per Carton     | 43.54 lbs / 19.75 kg   |



Altitude EARHEM401

### PRODUCT TESTING

|                                |             |                      |
|--------------------------------|-------------|----------------------|
| Chemical Resistance            | ASTM F 925  | Passed               |
| Critical Radiant Flux          | ASTM E 648  | Class I, $\geq 0.45$ |
| Dimensional Stability          | ASTM 2199   | Passed               |
| Residual Indentation           | ASTM F 1914 | Passed               |
| Resistance to Heat             | ASTM F 1514 | Passed               |
| Resistance to Light            | ASTM F 1515 | Passed               |
| Smoke Density                  | ASTM E 662  | Passed               |
| Static Load Limit              | ASTM F 970  | Passed               |
| Static Coefficient of Friction | ASTM D 2047 | Passed               |




**PREMIUM**  
WEAR LIMITED WARRANTY




Altitude EARHEM401



Boundary EARHEM404 (Heavy Shade Variation)



Ozone EARHEM405 (Heavy Shade Variation)



Jet Stream EARHEM406 (Heavy Shade Variation)



Thermal EARHEM407 (Heavy Shade Variation)



Level Up EARHEM409 (Heavy Shade Variation)

\*All measurements are nominal. Sound Testing will vary depending on the specific floor/ ceiling assembly.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images.

Please visit [www.earthwerks.com](http://www.earthwerks.com) for full warranty details & installation guidelines. All specifications & offerings are subject to change without notice.