



ALARA® PLUS

Classification	Resilient flooring in modular format with Solid Polymeric Core
Size*	7" x 48.6" (nom)
Overall Thickness*	5 mm (includes 1 mm cushion backing)
Wear Layer	20 mil / 0.50 mm, featuring CliffShield MAX finish with anti-microbial protection
Edge	4 side Bevel
Standard Colors	5 standard colors
Installation Method	Fold Down
Wear Limited Warranty	Lifetime Residential / 30-Year Light Commercial
Recycle Content	This product contains no recycled content. 100% recyclable post-use
Packaging	23.66 ft ² per carton 10 pieces per carton 55 cartons per pallet
Weight Per Carton	40.96 lbs



Park City CW-1351

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648	Class I, CRF >0.45
Dimensional Stability	ASTM F 2199	Passed
Residential Indentation	ASTM F 1914	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Static Load Limit	ASTM F 970	Passed
Thickness Overall	ASTM F 387	Passed
+STC Sound Testing	ASTM E 90 / E 413	68
+IIC Sound Testing	ASTM E 492 / E 989	66



CW 330 - Breckenridge



CW 5026 - Snowshoe



CW 1500 - Sugarloaf



CW 263 - Keystone



CW 1351 - Park City

*All measurements are nominal. +Sound Testing will vary depending on the specific floor/ ceiling assembly.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images.

Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.