



Ivory Coast

Spec and Test Info

Dimensions 6" x 48"

Thickness 6.55 mm with 1 mm high density pad-attached

Pad Type EVA

Wear Layer 12 mil Enhanced

Sq. Ft. / Box 31.52

Box Weight 50 Lbs/Box

Commercial Warranty 4 Year Light

Residential Warranty 25 Year

Moisture Warranty Limited Lifetime

Structure Warranty Limited Lifetime

Construction Engineered Vinyl Composite

Installation Method Float or Glue Down

Finish UV-Cured

Installation Grade Above, On and Below

Locking Method Valinge

Edge Profile Micro Bevel



Slate
WP 601 SL-N



Hazel
WP 602-HZ



Tawny
WP 603 TW-N



Sepia
WP 604 SP-N

ASTM-E 648	Critical Radiant Flux	Meets or Exceeds, Class 1
ASTM E 492-09	Impact Sound Conduction	IIC 59 db
ASTM 90-09	Airborne Sound Conduction	STC 63 db
ASTM C 518	Thermal Resistance	R Value – 0.57
NALFA 3.2	Thickness Swell	Class 4, Heavy Commercial
NALFA 3.3	Xenon Light Resistance	Class 4, Heavy Commercial
NALFA 3.4	Cleanability-Stain Resistance	Class 4, Heavy Commercial
NALFA 3.5	Large Ball Impact Resistance	Class 4, Heavy Commercial
NALFA 3.6	Small Ball Impact Resistance	Class 4, Heavy Commercial
NALFA 3.8	Dimensional Tolerance	Class 4, Heavy Commercial
NALFA 3.9	Caster Chair	Class 3, Commercial
NALFA 3.10	Surface Bonding	1.31N/mm – Exceeds Class 3 Commercial Requirement
ASTM C 1028-96	Static Coefficient of Friction	0.68 (Slip Resistance) Passes ADA/OSHA Standard
ASTM F 970-07	Static Load Limit	0.004 inch – Passes at 500 psi
ASTM F 2753	Rolling Load Over Resilient FC	0.024 inch
ASTM F 1514	Color Resistance to Heat	Meets <8.0 Delta E Requirement
ASTM F 1515	Color Resistance to Light	Meets <8.0 Delta E Requirement

Certifications: Carb Compliant, Contributes to LEED Credits, California 01350 Compliant, GREENGUARD GOLD Certified, Phthalates Free

Environmental Statement: We are committed to providing consumers and specifiers with beautiful and durable floors at a good value, while minimizing our impact on the environment and enhancing and improving whenever possible

