



## CHASSIS® PRO SPC PLUS

Classification	ASTM F-3261 Resilient flooring in modular format with Solid Polymeric Core
Size*	7" x 48" / 183 mm x 1220 mm
Overall Thickness*	0.20" / 5 mm (4 mm + 1 mm cushion backing)
Wear Layer	20 mil / 0.50 mm featuring <b>Diff Shield MAX</b> finish
Edge	Bevel
Standard Colors	8 colors
Installation Method	Angle/Angle
Wear Limited Warranty	Lifetime Residential
Recycled Content	This product contains no recycled content.
Packaging	28.84 ft² (2.68 m²) per carton 12 pieces per carton 45 cartons per pallet
Weight Per Carton	49.45 lbs / 22.43 kg



Axle - CHS-5465CB

### PRODUCT TESTING

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648	Class I, >1.13
Dimensional Stability	ISO 23999	Passed
Residual Indentation	ASTM F 1914	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662	Passed
Static Load Limit	ASTM F 970	Passed
Slip Resistance	ASTM C 1028	Passed
STC	ASTM E 90 / E 413	56
Delta IIC	ASTM E 2179	29



PREMIUM I Wear Limited Warranty




Axle CHS-5465CB




Clutch CHS-5466CB




Caspas CHS-5479CB



Armature CHS-5480 CB (Heavy Shade Variation)



Motorcoach CHS-5481CB



Suspension CHS-5482CB



Spitfire CHS-5487CB (Heavy Shade Variation)



Backbone CHS-5488CB (Heavy Shade Variation)

\*All measurements are nominal. Sound Testing will vary depending on the specific floor/ ceiling assembly.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images.

Please visit [www.earthwerks.com](http://www.earthwerks.com) for full warranty details & installation guidelines. All specifications & offerings are subject to change without notice.