



- ▶ Made of **HIGH-DENSITY SYNTHETIC RUBBER**
- ▶ For use under today's popular **MLF/LVT/Rigid Core with attached back, Laminate, Sheet Vinyl, Engineered, and Solid Hardwood flooring**

Don't get stuck with a noisy floor

Leggett & Platt® Flooring Products

# Whisper Step®

## Acoustical Underlayment

### Xtreme™ Protection



#### Noise Guard

Reduces impact and airborne noise in-room and between floors. Reduces up to 10 decibels of in-room noise and an overall improvement between floors of 25%.



#### Block-out® Moisture Guard

Prevents spills from getting into subfloor and allows moisture vapor to escape from beneath.



#### Mold & Mildew Guard

Fresh Dimension® antimicrobial works to inhibit the growth of mold, mildew, and odor-causing bacteria.

### Xtreme™ Performance



#### Comfort

Makes hard-surface flooring more enjoyable.




#### Support

The class leading extreme density not only resists compression but will perform for the life of the floor.




#### Easy Installation


Lays flat and helps mask minor subfloor irregularities; can be used above and below grade.



Flooring over Whisper Step®



Flooring over lightweight underlayment



# Whisper Step®

## Acoustical Underlayment

### SPECIFICATIONS

Composition:	Made of High-Density Synthetic Rubber	
Density:	62 lbs/ft <sup>3</sup> or 42 oz/yd <sup>2</sup>	
Shore A Hardness:	70 ASTM D2240	
IFD @ 25%/65%:	677.2 lbs/5,000+ lbs	
Thickness:	0.056" (1.42 mm)	
Color:	Green	
R-Value:	0.02	
Moisture Barrier:	Block-Out® Moisture Guard	
Permeance*:	1.151 ASTM E96	
Water Vapor Emission	0.252 lbs/1000 ft <sup>2</sup> /24 hr ASTM E96	
Castor Durability Test:	Passes 25,000 Cycles**	
Product Codes:	BM0042	BM0040
Dimensions:	36" x 33.33'	54" x 44'
Ft <sup>2</sup> /Roll:	100	200
Yd <sup>2</sup> /Roll:	11.11	22.22
Roll Weight:	29 lbs	58 lbs

### ACOUSTICAL PROPERTIES

Impact Insulation Class (IIC):	66*** ASTM E492 / E989
Δ IIC:	22 ASTM E2179
Sound Transmission Class (STC):	63*** ASTM E90 / E413

### PROTECTION

Indoor Air Quality:	Passes California Section 01350 for low VOC emissions
Antimicrobial:	Yes

### LIMITED WARRANTY

Please visit [LPFlooringProducts.com/whisper-step](http://LPFlooringProducts.com/whisper-step) for detailed warranty information.

\* Conduct moisture tests in accordance with flooring manufacturer installation guidelines and requirements

\*\* Passes Castor Durability Test for 25,000 cycles when tested under minimum of 3 mm double-glued luxury vinyl plank and minimum 3.2 mm floating-click

\*\*\* When tested with floor-ceiling assembly (6" concrete slab)

Shore A Hardness: ASTM D2240  
 IFD: ASTM D3574  
 Permeance: ASTM E96  
 IIC: ASTM E492-09 / ASTM E989-06  
 Δ IIC: ASTM E2179-03  
 STC: ASTM E90 / ASTM E413-10

