

Brake operation:- Foot	4 wheels.
Hand	Rear wheels
Wheel Brake Drum, sizes	305 m/m
Road springs, type	Semi Elliptic
Road springs, anchorage	Silent bloc bushes (no lubrication required).
Shock absorbers fitted	Front and Rear
Rear axle, type.	Semi-floating
Tyres (Dunlop) size	29 x 5.25.
Wheelbase and track.	9'6" x 4'8".
Overall length and width	13'7" x 5'8 $\frac{1}{2}$ ".
Ground clearance. 8".	
Turning circle.	42'.
Weight of coachbuilt saloon,	
Unladen (ready for road).	1 ton. 6 $\frac{3}{4}$ cwt.

BODY STYLES & PRICES.

Tourer) Beige & Maroon	£310	
Safety Tourer) Grey & Blue	£325
) Fawn & Nutria	
Saloon) Maroon & Beige	£325	
Safety Saloon) Blue & Grey	£375
) Nutria & Fawn	
+ Four Door Segrave Coupe	Green & Beige	£385	
	Black & Primrose		
+ Six Light Weymann Saloon	Brown	£375	
	Black & Red		
Drop Head Coupe) Maroon & Beige	£415	
) Blue & Grey
) Nutria & Fawn

= + Sunshine Roof can be fitted at an extra charge of £10.

N.B. Wire wheels can be fitted to Standard Models at an extra charge of £10.

Artillery wheels can be substituted for wire wheels on Safety models.

BRAKES.

According to an early Ferodo Brake Lining Catalogue, the 1931 Hillman Fourteen had different sizes of linings from the 1930 model. This probably means the late 1930 Hillman Fourteen, so it is as well to check with one's own shoes before using these dimensions when ordering linings.

Front - Foot (4 shoes).

Drum diameter	12"
Length	13 $\frac{5}{8}$ "
Width	1 $\frac{1}{2}$ "
Thickness	$\frac{3}{4}$ "
Inside radius	5 23/32".

Rear - Hand & Foot (8 shoes)

Drum diameter	12"
Length	13 $\frac{1}{2}$ "
Width	1 $\frac{3}{4}$ "
Thickness	$\frac{1}{2}$ "
Inside radius	5 23/32"