

DANDUX SOLID WOVEN COTTON BELTING

DANDUX Model	Number of Plies	Yarn	Standard Widths (inches)	Tension Rating (lbs/in W)	Nominal Thickness	Minimum Pulley Diameter	Temp. Range Continuous	Temp. Range Intermittent
812C2	2	Cotton	1-52	55	3/32"	1 1/2 "	-60° F to 225° F	300° F
812C3	3	Cotton	1-48	75	1/8"	2"		
812C4	4	Cotton	2-48	100	3/16"	3"		
812C5*	5	Cotton	*	125	7/32"	4 1/2 "		
812C6*	6	Cotton	*	145	1/4"	6"		

DANDUX AIRSLIDE SOLID WOVEN POLYESTER BELTING

81W1	3	Poly	2-52	280	3/16"	4"	-60° F to 225° F	250° F
81W2	4	Poly	2-52	550	1/4"	8"		
81W6	6	Poly	2-52	500	1/4"	8"		

*C5/C6 Not Available – Info for Reference only

HIGH TEMPERATURE AIRSLIDE PRODUCTS

DANDUX Model	Construction/ Material	Thickness	Weight (lbs/sq.ft.)	Temperature	Tensile Strength (Warp/Weft)
81WFT	Solid Woven Fiberglass	.255 In.	1.6	800 °F	3000 lbs./ 900 lbs. per inch
81WAD	Solid Woven Para-Aramid (e.g. Kevlar)	0.19 In	0.8	-76 to 482 °F Short dur'n: 662 °F	2200 lbs. / 2300 lbs. per inch
81WAN	Solid Woven Meta-Aramid (e.g. Nomex)	0.19 In	0.7	-76 to 482 °F Short dur'n: 572 °F	2200 lbs. / 2300 lbs. per inch

DANDUX AERATION PADS FOR TRAILERS

Trailer Manufacturer	DANDUX Model	Material	Diameter	Plies	Overall Thickness
HEIL	1812-C	COTTON	30.5"	2	3/32"
	1812-P	POLYESTER	30.5"	3	3/16"
FRUEHAUF	TKS 8807C	COTTON	13"	6	1/4"
	TKA 8808C	COTTON	19.625"	6	1/4"
	TKA 8898C	COTTON	30"	6	1/4"
	TKS 8807P	POLYESTER	13"	3	3/16"
	TKA 8808P	POLYESTER	19.625"	3	3/16"
	TKA 8809P	POLYESTER	30"	3	3/16"
	TKA 8856P	POLYESTER	30.813"	3	3/16"
TRAILMOBILE	TKT 8898C	COTTON	36"	3	3/16"
	TKT 8807P	POLYESTER	36"	3	3/16"
	TKT 8808P	POLYESTER	36"	2	1/8"
BUTLER	B-074086	COTTON	34"	3	N/A
	B-074086	POLYESTER	34"	3	3/16"
	B-074086	POLYESTER	34"	2	1/8"

CUSTOM SIZES and PATTERNS AVAILABLE for

- TRAILERS
- SILOS
- BINS

C.R.DANIELS, INC. CONVEYOR BELTING AND SPECIALTY FABRICATIONS

Corporate Headquarters 3451 Ellicott Center Drive, Ellicott City, MD 21043
DANDUX BELTING NORTH AMERICAN SALES 92 McLaren St., Red Bank, NJ 07701
www.crdaniels.com

CALL TOLL FREE 1-800-933-2638 Direct 732-741-4609 Fax 866-212-2366