

# FOOD BELTING

We make your job easier by having a large inventory of standard belts for food handling. All meet appropriate FDA, USDA requirements. They are cleaned easily with warm water and detergent and are resistant to many oils and chemicals. Ideal for conveying meat, poultry, seafood, fruits, vegetables, bakery products, snack foods, tobacco and cereals.

SPECIALTY FABRICATIONS including a wide range of carefully cleated and vulcanized belts will satisfy your special needs.

Name & Style Number	Plies	Cover Compound	Tension Rating Lbs. P.I.W.	Nominal Thickness			Min. Pulley Dia.	Nominal Weight Lbs. P.I.W./Ft.	Slab Width	Recommended Lacing	
				Cover	Bottom	Overall				Alligator	Clipper
Temp. range 10° F-250° F except PVC & urethane 0° F-200° F & Butyl as noted											
<b>Super-Kleen</b>											
SK92	2	White Nitrile	35	3/64"	F.S.	7/64"	2"	.058	72"	7	1
SK93	3	White Nitrile	52	3/64"	F.S.	9/64"	2½"	.077	72"	15	1
SK94	4	White Nitrile	70	3/64"	F.S.	11/64"	3"	.096	72"	20	2
SK105	3	White Nitrile	105	3/64"	F.S.	9/64"	2½"	.080	72"	15	1
SK135	3	White Nitrile	135	3/64"	F.S.	9/64"	3"	.080	72"	15	1

## CLEATS, FLANGES & V-GUIDES FOR FOOD/PACKAGE HANDLING BELTS


**NITRILE** — The superior quality of hot vulcanized cleats, flanges and V-Guides is recommended and used wherever practical. Sometimes hot vulcanizing is not practical... in those cases we bond with adhesive or recommend mechanically fastened accessories.

**PVC** — We utilize a hot-melt bonding system to permanently attach PVC cleats, flanges and V-Guides wherever practical... otherwise we use an adhesive bond or a combination of adhesive/hot melt.

**NOTE:**


Supply all information possible with your order/inquiry including product carried, temperature/chemical requirements and pulley diameters.

### STURDI SMOOTH FABRIC REINFORCED



Heights to 3"

### HOT VULCANIZED T-CLEATS



Full width, recessed or split—  
Heights to 3"

### FLEXI-FLANGE



Plain, slotted or slotted & drilled.  
Heights... ½", ¾", 1"

### NEW LINEAR THERMOPLASTIC FOOD GRADE BELTS



CALL FOR INFORMATION  
1-800-933-2638



Name & Style Number	Plies	Cover Compound	Tension Rating Lbs. P.I.W.	Nominal Thickness			Min. Pulley Dia.	Nominal Weight Lbs. P.I.W./Ft.	Slab Width	Recommended Lacing	
				Cover	Bottom	Overall				Alligator	Clipper
Teflon Super-Kleen TSK92	2	Teflon	60	2 mil.	F.S.	1/16"	1 1/2"	.028	48"	00	1D
Butyl Super-Kleen -65° to +300° F SK93BTL	3	White Butyl	90	1/32"	F.S.	3/32"	Hot 1 1/2" Cold 4"	.053	72"	7	1A
Mini Cleat MC135	3	White Nitrile	135	3/64"	F.S.	15/64"	2"	.075	58"	15	1
Waffle-Top WT92	2	White Nitrile	60	1/16"	F.S.	7/64"	2"	.050	72"	7	1A
Tyler Wire TW93	3	White Nitrile	52	1/16"	F.S.	9/64"	2 1/2"	.077	72"	15	1
Check-Out Counter CO92PVC	2	Black PVC	60	1/64"	F.S.	5/64"	1 1/2"	.035	72"	1A	1D
SUP-R-THANE F.D.A. 45CCOS	1	Clear Ureth.	45	1/32"	F.S.	1/16"	1"	.030	72"	00	25LP
100CCOS	1	Clear Ureth.	100	1/32"	F.S.	5/64"	1 1/2"	.045	72"	1A	1D
125CCOS	1	Clear Ureth.	125	1/32"	F.S.	9/64"	2"	.070	72"	7	1
										or Finger Splice	
PVC CHEVRON FDA125CHV	1	White PVC	125			7/32"	3"	.090	72"	20	2
FDA125COS	1	White PVC	120	Smooth	F.S.	9/64"	2 1/2"	.075	72"	15	1
Monofilament UW3402	1	White Ureth.	34	.002"	Bare	.028"	Nose Bar	.012	60"	Finger Splice	
PW3405	1	White PVC	34	.005"	Bare	.035"	Nose Bar	.017	60"	or Bias Splice	
UW6802	2	White Ureth.	68	.002"	Bare	.051"	1 1/4"	.023	60"	Preferred	
PW6805	2	White PVC	68	.005"	Bare	.079"	2 1/2"	.035	60"	... Inquire.	

### EXPERT FABRICATION OF LACED, CLEATED AND VULCANIZED ENDLESS BELTS

#### BAKERY BELTS FOR:

BAGEL MACHINES	DEPANNERS	MODEL K'S
BUN SLICERS	DIVIDERS	PAN-O-MATS
COOLING CONVEYORS	MAKE UP TABLES	PROOFERS
CUTTERS	METAL DETECTORS	SHEETERS
PAN RETURN	MOULDERS	WRAPPERS

#### OTHER FOOD PROCESSORS

BOTTLERS	MEAT PACKERS
BREWERS	POULTRY PLANTS
CONFECTIONERS	SEAFOOD
CANNERS	SNACK FOODS
FROZEN FOODS	TOBACCO
FRUITS	VEGETABLES