



DURALON RUBBER COVERED BELTING

Style	Covers	Nominal O. A. T. (Inches)	Nominal Weight PIW / Ft	Minimum Pulley Diameter
2-Ply 220	1/8 x Bare	.231	.128	16"
2-Ply 220	1/8 x 1/16	.294	.150	16"
2-Ply 220	3/16 x Bare	.294	.150	16"
2-Ply 220	3/16 x 1/16	.356	.182	16"
2-Ply 220	1/4 x 1/16	.419	.214	16"
3-Ply 330	1/8 x Bare	.284	.158	18"
3-Ply 330	1/8 x 1/16	.347	.190	18"
3-Ply 330	3/16 x Bare	.347	.190	18"
3-Ply 330	3/16 x 1/16	.409	.222	18"
3-Ply 330	1/4 x Bare	.409	.222	18"
3-Ply 330	1/4 x 1/16	.472	.254	18"
4-Ply 440	3/16 x 1/16	.442	.294	21"
4-Ply 440	1/4 x Bare	.442	.294	21"
4-Ply 440	1/4 x 1/16	.505	.326	21"
4-Ply 440	3/8 x 1/8	.692	.422	21"

COVER COMPOUNDS	Style	Description	Durometer
	GRADE 1	High Abrasion	64
	GRADE 2	Normal Heavy Use	60
	Hot Stock	300 Deg. SBR	63
	MOR	MOR Nitrile/SBR	62
	MSHAU	MSHA Underground	66



CALL US TO REVIEW YOUR REQUIREMENTS FOR:

- HOLE PATTERNS
- FLANGES / CLEATS
- V-GUIDES
- BUCKETS



C.R.DANIELS, INC. CONVEYOR BELTING AND SPECIALTY FABRICATIONS

Corporate Headquarters 3451 Ellicott Center Drive, Ellicott City, MD 21043
DANDUX BELTING NORTH AMERICAN SALES 92 McLaren St., Red Bank, NJ 07701
www.crdaniels.com

CALL TOLL FREE 1-800-933-2638 Phone 732-741-4609 Fax 732-741-4196