

2018 ECO STOCK RULES:

Driver's Age requirements: 13 years or Older with Minor's Release Notarized by Both parents.

Engine Option 1- Domestic

- Any domestic front wheel drive vehicle except Dodge Neon
- 3.4 liter engine maximum push rod only on V-6
- Factory automatic transmission

Engine Option 2- Import:

- Any import front wheel drive vehicle with four (4) doors
- 2.4 liter engine maximum
- No twin Cams allowed: No V-techs allowed
- Factory automatic transmission

Tires & Wheels:

- Tires must be DOT approved
- Series rating on tire must be 55 series or higher and must be legible on side of tire
- Tires must be inflated to at least 30 PSI
- Three tires must be the same size. One tire may be larger or smaller by one size on the rear of the car.
- All 4 factory wheels must be the same size and offset. No Aftermarket racing wheels.

General rules-Applies to Domestic and Import Vehicles Racing:

- 1. Unaltered VIN plate must be on vehicle
- 2. Factory rated horsepower only
- 3. Vehicle must have come from factory with a back seat
- 4. Car must be completely factory stock. No aftermarket parts of any kind allowed.
- 5. No turbos or supercharges allowed.
- 6. Antifreeze may be run in vehicle.
- 7. Only seats, carpet, door panels, headliner and catalytic converter may be removed.
- 8. All lights, lenses, flammable interior components and factory mirrors must be removed.

Suspension:

May camber right front wheel only to help with tire wear. Camber is only alternation permitted. No cutting, lengthening
and re-welding permitted. May slot bolt holes. No additional bracing.

Roll Cage:

- 1. Minimum of four (4) point cage with three (3) driver door bars mandatory. 1.5" .095 tubing minimum. Driver must have adequate arm clearance between seat and door bars to ensure safety.
- 2. No down bar or bracing placed struts towers
- 3. Steel door plate, minimum 18 gauge or .049 " Required to protect driver from debris. Minimum dimensions 12 inches high and 24 inches long.
- 4. Radiator Loop constructed of max size 1.5" OD by .095" wall thickness and installed between frame horns.
- 5. Wrecker tow chain recommended in front and rear of car.
- 6. Battery may be relocated to the trunk of car installed in a metal battery holder securely fastened to body or cage or remain in factory location and be securely mounted.
- 7. All windows except front windshield must be removed. If windshield is removed, must have at least three bars in front of driver in windshield area.

Safety:

- 1. No 2-seater vehicles allowed
- 2. Helmet must be full-faced racing type helmet with a minimum of SNELL 95 or SA 2000 rating. Date must be within the last 5 years.
- 3. SFI fire retardant drivers suit required (Nomex underwear is strongly recommended also)
- 4. Racing gloves & shoes required
- 5. Fire extinguisher must be mounted and fully charged with drivers reach
- 6. Driver's side quick release or push button window net required
- 7. Quick release steering wheel allowed
- 8. Removal of airbags highly advised

Vehicle must remain factory stock!!! Nothing else other than what is listed above may be altered, removed, changed and ect.

CLAIM RULE:

After competing in three races, vehicles are subject to be claimed by anyone including spectators after the race for \$ 1800. Claim does not include the driver's seat, seat belt, window net, transponder& fire extinguisher.