

105 SPEEDWAY 2020 STREET STOCK RULES

FRAME AND SUSPENSION:

- FRAMES MUST BE STOCK FRONT TO REAR, UNI-BODY CARS MAY CONNECT SUB FRAMES. X-BRACING ALLOWED. ALL CARS MUST REMAIN WITH 5/8" OF STOCK WHEEL BASE OF CAR BEING RACED. WHEEL BASE MUST MATCH THAT OF FRONT CLIP BEING RACED, AND REAR SUSPENSION MUST MATCH FRONT.SUSPENSION
 1. EX. 70'S CAMARO FRONT CLIP MUST HAVE LEAF SPRING REAR SUSPENSION
 2. EX. METRIC FRAME MUST USE COIL SPRING REAR SUSPENSION
 3. MAY USE DURRENCE LAYNE STREET STOCK LEGAL REPLACEMENT FRAME
- FRONT SUSPENSION
 1. MUST USE STOCK MOUNT STEERING BOX OR STOCK MOUNT RACK AND PINION FOR FRAME BEING RACED IN STOCK LOCATION
 2. MUST USE STOCK LOWER CONTROL ARM MOUNTS IN STOCK LOCATION
 3. MUST USE STOCK OR TUBULAR STOCK REPLACEMENT LOWER CONTROL ARMS
 4. NO COILOVERS
- REAR SUSPENSION
 1. MUST USE STOCK SUSPENSION MOUNTS ON CHASSIS
 2. LEAF SPRING REAR SUSPENSION MAY USE FABRICATED MOUNT IN STOCK LOCATION
 3. NO AFTERMARKET TRAILING ARMS ALLOWED, MUST BE SOLID
 4. ANY LEAF SPRING ALLOWED
 5. ANY REAR END ALLOWED, MUST BE LOCKED
- ENGINE LOCATION
 - a. MUST BE MOUNTED NO FARTHER BACK THEN ONE INCH BEHIND #1 SPARK PLUG HOLE AT CENTERLINE OF UPPER BALL JOINT

BODY:

- ALL CARS MUST RESEMBLE A STOCK CAR
- NO LATEMODEL BODIES ALLOWED
- MUST USE AFTERMARKET PLASTIC NOSE PIECE. NO LATEMODEL NOSES ALLOWED.
- 8" SPOILER MAX

ENGINE:

- ANY ENGINE WITH SINGLE CARBURETOR ONLY
- GASOLINE/RACE GAS ONLY-NO METHANOL/ALCOHOL OR E-85
- MUST BE SELF STARTING-NO PUSH START

TRANSMISSION:

- MUST HAVE A MINIMUM FORWARD, REVERSE AND NEUTRAL GEARS

WHEELS AND TIRES:

- 10" WIDE WHEELS MAXIMUM
- ANY TIRE ALLOWED

ADDITIONAL CLASS RULES ACCEPTED

- DURRANCE LANE
- LONE STAR STREET STOCK
- IMCA STOCK CAR

