

# Striker Instructions



## SET UP

1. Select a stable, level area for set up.
2. Unhook trailer and lights from tow vehicle and roll to set up area.
3. Carefully raise the unit into its upright position. Assistance will be required.
4. Remove the nut from the and unlock the safety chain from the support legs and swing them down so that they are firmly resting on the ground. Then wrap the chain around the frame and lock. Stake the unit down securely. If it is not possible to stake down, then weigh the unit down with 800lbs on each side.

## OPERATION

1. Check to see that the unit is on a firm and level surface.
2. Inspect the mallet to make sure that the head is securely attached to the handle.
3. Block off a "striking zone" with plenty of room for the participant to safely swing the mallet with no danger of hitting a spectator or passer-by.
4. If the Easy Striker moves or "walks" during use, drive 4 stakes through the 4 holes on the sides of the unit.
5. The level of difficulty can be adjusted by raising or lowering the spacer under the back end of the high striker arm.

## TAKE DOWN

1. Raise the support legs and secure with the locking nut and wrap the safety chain around the frame to be certain the legs will not drop down while in tow.
2. Carefully lower the unit back onto its wheels. Assistance will be required.
3. Attach trailer to vehicle. Put pin or bolt through hitch release lever and secure. Attach safety chain to vehicle.

## CAUTION

1. Do not operate in high winds or storms.
2. Do not set up near power lines.
3. Be sure everyone is back a safe distance when the player is swinging the hammer.
4. Overall height/clearance is ~15 feet.
5. 2" ball hitch required for towing.