



# KC 500 NATURAL DEGRESEER

## APPLICATION:

**KC 500 NATURAL DEGRESEER** is recommended to be used on automobiles, 4WDs, motorcycles, boats, trailers, house exteriors, concrete driveways, greasy work gear, it also can be used on any surface, leaving a streak-free finish.

**KC 500 NATURAL DEGRESEER** is a balanced superior cleaner, containing a natural biodegradable solvent, surfactants, hard water chelators and coupling agents. This quick splitting natural degreaser rapidly liquefies, penetrates, dissolves and suspends oil, ink and grease permitting a simple water rinse to leave clean surface.

**KC 500 NATURAL DEGRESEER** leaves a pleasant smell.

No treatment prior to disposal is required.

**KC 500 NATURAL DEGRESEER** will also remove gear greases and in particular over lubricants from all metal parts.

**KC 500 NATURAL DEGRESEER** is 90% biodegradable in 28 days, this gives you a truly environmentally friendly product.

## USE INSTRUCTIONS:

Allow 10-20 minutes for **KC 500 NATURAL DEGRESEER** to permeate the dirt and grime before rinsing with water or steam jet.

### Sponge cleaning:

Dilute 1-part **KC 500 NATURAL DEGRESEER** with 100 parts of water for sponge application, or 2-3 caps per regular 9L bucket.

### Sprayer:

Mix 1-part **KC 500 NATURAL DEGRESEER** with 20 parts of water.

### Pressure washer:

For pressure washers or foam guns, mix 1-part **KC 500 NATURAL DEGRESEER** with 10 parts of water.

### Ultrasonic baths:

Mix 1-part **KC 500 NATURAL DEGRESEER** with 20 parts of water.

**KC 500 NATURAL DEGRESEER** can be made stronger or weaker as needed.

## CAUTION:

On **Aluminum, Magnesium Alloys, and Zinc** try undiluted on an inconspicuous area before cleaning.

Protect from cold and heat.

This technical information does not admit legal responsibility for its content.

**PHYSICAL PROPERTIES:**

Density (20 ° C) > 1.05 to 1,10 g / c.c. DIN 51757

pH=8-9

Viscosity (20 ° C) 500-600 CP