



SUPER WASH

APPLICATION:

SUPER WASH is recommended to be used on automobiles, 4WDs, motorcycles, boats, trailers, house exteriors, concrete driveways, greasy work gear, it also can be used on any surface, leaving a streak-free finish.

SUPER WASH was designed to be safe for all materials found on cars and other motor vehicles and hard surfaces, such as aluminum, brass, copper, glass, plastic, rubber, neoprene, and vinyl.

SUPER WASH is a concentrated pH-neutral, biodegradable, non-caustic rust, corrosion inhibitor heavy-duty cleaning gel that cleans up the toughest grease, oil, and soot.

USE INSTRUCTIONS:

Allow 10-20 minutes for **SUPER WASH** to permeate the dirt and grime before rinsing with water or steam jet.

Sponge cleaning:

Dilute 1-part **SUPER WASH** with 100 parts of water for sponge application, or 2-3 caps per regular 9L bucket.

Sprayer:

Mix 1-part **SUPER WASH** with 20 parts of water.

Pressure washer:

For pressure washers or foam guns, mix 1-part **SUPER WASH** with 10 parts of water.

SUPER WASH can be made stronger or weaker as needed.

CAUTION:

Protect from cold and heat.

PHYSICAL PROPERTIES:

Density (20 ° C) > 1.05 to 1.10 g / c.c. DIN 51757

pH=7-8

Viscosity (20 ° C) 500 CP

This technical information does not admit legal responsibility for its content.