


REF. 3444 DUOX PLUS VEO TELEPHONE



The VEO telephone is made of high-impact ABS plastic. Texturized finish for easy cleaning and ultraviolet protection to get more resistance to the light. Its unique handset design incorporating a magnet enables the user to put it back into position correctly when the call is finished. Its balanced design of pure lines is distinguishing, modern and minimal. VEO integrates in the ambience.

When receiving a call and the handset is picked up a conversation with the visitor can take place. The conversations is automatically cut off after 90 seconds, or when the handset is put back in position. To open the door, press the button .

ACCESORIOS



Ref. 3749



Ref. 3388



Ref. 3389

DESKTOP

3749 VEO/LOFT TELEPHONE DESKTOP SUPPORT

Fermax desktop support allows a call from the entrance to be answered from the office desktop. Manufactured in the highest quality stainless steel (AISI 316L).

REPLACEMENT

Universal frames with an extra slim format, manufactured in a high resistant ABS plastic with a texturized finish. In replacement works, allow to cover the space left by older equipment. In addition, it keeps the wall protected from the dirt produced by the use of telephones and monitors.

3388 UNIVERSAL FRAME

Dimensiones: 120 x 249 x 10 mm

3389 UNIVERSAL FRAME LARGE

Dimensiones 210 x 240 x 10 mm

Handset with induction loop 

3443 VEO TELEPHONE HANDSET W/INDUCT.LOOP

GENERAL CHARACTERISTICS	3444
Technology	DUOX PLUS (non-polarised 2 wire full digital system)
Audio/Video system	Audio
Set-up (Installation)	Surface mounted
Desktop support	Yes (ref. 3749)
Handset with magnet to facilitate the hang up	Yes
Induction loop	Replace the handset with ref. 3443
Color of the product	Matt white
Number of pushbuttons	1
Kind of pushbuttons	Mechanical
Number of leds for lighted indications	-
PROGRAMMING OF THE TERMINAL ADDRESS	
From the terminal	-
From the outdoor panel or guard unit	Yes
From the outdoor panel throughout the apartment door bell	Yes
FEATURES	
Guard unit call	Yes (by means of the door release button)
Auto-on	Yes (with panel nº 0 of the own block or with the last panel from where a call has been produced and during the 30 s. after the finalization of the same)
Additional function F1	-
Additional function F2	-
Apartment door bell differentiated from the outdoor panel	Yes
Connection for additional devices (call extension, light/buzzer activator, etc.)	Yes (ref. 2040, ref. 2438, ref. 3267)
Additional terminals on the same address	Yes, max. 2 additional terminals (additional power supply can be required)
Doormatic (automatic door release for offices, etc.)	-
ADJUSTMENTS	
Ring tones selection	Yes (5). Configurable according to origin: Panels or Concierge unit
Call volume control	Yes (3 positions switch)
Do-not-disturb mode	Yes (3 positions switch). Indicated by a red mark.
Audio volume control	-
TECHNICAL FEATURES	
Product dimensions (width x height x depth) mm	82 x 214 x 43
Time to answer or open the door since the call is done	30 s.
Conversation time	90 s.
Conversation privacy	Yes
Voltage	18-24 Vdc
Maximum consumption	3,5 W
Standby consumption	0,3 W
Working temperature (°C, °F); Humidity	[-5°C, +40°C][23°F, 106°F]; [0%, 90%]
Line adaptor included in the terminal	Yes (A, C, default position OFF)
Connections	-, A, T, B, B