



# **EX SERIES** **EXTENDIBLE TAIL HOIST**

The Extendible Tail Hoist (EX Series) has a sliding tail that provides operators the option of loading in areas with low overhead clearance. GALFAB offers this hoist with an 8" mainframe and 2" subframe or the very popular 10" sub frameless hoist. Available in 60k and 75k pound models to fit any application.

# THE GALFAB **ADVANTAGE**



## Outboard Supported Side Rollers

Greasable Roller shaft is removable with two bolts for ease of replacement and maintenance.



## Low Loading Angle

An 80" tail provides a low loading angle.



## Optional Side Roller on Tail

Optional Side Roller on Tail Ease of container loading and unloading.



## Optional Wings on Tail

Optional Wings on Tail Additional guide for container loading.

## STANDARD FEATURES

- 8" x 4 x 3/8" Main Frame Tube
- 1/2 inch x 3 1/2 inch Wear Strip on Top
- 3" x 2" x 1/4" Sub Frame
- 2 1/2" Diameter Rear Hinge
- All Working Points Greaseable
- Pintle Ready Apron
- 1" Spring Loaded Container Locks
- 2 1/2" Diameter Lift Cylinder Shafts
- Interchangeable 10" Vertical and Horizontal Sheaves
- 3/8 inch x 3 inch Winch Cylinder Rod Covers
- 6 Inboard and Outboard Supported Outside Rollers
- 48 Gallon Oil Reservoir with Sight and Temperature Gauge
- 25 Micron Filtration
- Inside and Outside Controls
- Choice of Forward or Reverse Mount Single Stage or Telescopic Lift Cylinders
- LED Lighting System
- 7/8" Cable with Heavy Duty Swivel Eye Hook
- 80 inch Extendible Tail
- No DOT bumper
- Front Mount Pump
- Hoist Up Warning Light
- Sealed Wiring System
- Hoist Up Alarm
- Backup Alarm

## OPTIONAL FEATURES

- Behind Cab and Oversize Oil Tanks
- Tool Boxes
- Auxilliary Stops
- Poly or Steel Fenders
- Aluminum Fenders
- Tarping Systems
- Hooker Hold On Systems
- Ratchet Tie Down Straps
- PTO
- Drop Shaft
- Integrated hydraulics can be used, if hydraulic tarping system is used
- Rear View Camera Systems
- Work Lights
- Onboard Scale Systems



**"The Hooker"  
Container  
Securement System**



**Auxillary fold down  
stops**



**Hydraulic Reservoirs**



**Tool Boxes**



**Poly, Steel &  
Aluminum Fenders**

Shop all replacement parts at:

**GALFAB.com**



Visit our website: [GALFAB.com](http://GALFAB.com) | Follow us on social media



| Call Today: 574-946-7767

# EX SERIES MODELS

| Model         | Capacity | CA   | CA with tarp | Length  | Dump Angle Tail Retracted | Load Angle Tail Extended | Up (sec)* | Down (sec)* | On (sec)* | Off (sec)* | Lift Cylinder       | Winch Cylinder     | Container Length ft | Apx Weight lbs |
|---------------|----------|------|--------------|---------|---------------------------|--------------------------|-----------|-------------|-----------|------------|---------------------|--------------------|---------------------|----------------|
| EX60174S072   | 60,000   | 174" | 186"         | 19' 10" | 48°                       | 27°                      | 27        | 15          | 41        | 28         | 6" x 4" x 72" DA    | 7" x 4" x 79.5" DA | 18'-22'             | 7,550          |
| EX60174S072R  | 60,000   | 174" | 186"         | 19' 10" | 48°                       | 27°                      | 27        | 15          | 41        | 28         | 6" x 4" x 72" DA    | 7" x 4" x 79.5" DA | 18'-22'             | 7,550          |
| EX60174T121   | 60,000   | 174" | 186"         | 19' 10" | 48°                       | 27°                      | 35        | 29          | 41        | 28         | 6"-5"-4" x 121" DAT | 7" x 4" x 79.5" DA | 18'-22'             | 7,225          |
| EX75174S072F7 | 75,000   | 174" | 186"         | 19' 10" | 48°                       | 27°                      | 37        | 23          | 41        | 28         | 7" x 4" x 72" DA    | 7" x 4" x 79.5" DA | 18'-22'             | 7,550          |
| EX75174S072R7 | 75,000   | 174" | 186"         | 19' 10" | 48°                       | 27°                      | 37        | 23          | 41        | 28         | 7" x 4" x 72" DA    | 7" x 4" x 79.5" DA | 18'-22'             | 7,550          |
| EX75174T121   | 75,000   | 174" | 186"         | 19' 10" | 48°                       | 27°                      | 35        | 29          | 41        | 28         | 6"-5"-4" x 121" DAT | 7" x 4" x 79.5" DA | 18'-22'             | 7,350          |
| EX60194S072   | 60,000   | 194" | 206"         | 21' 5"  | 48°                       | 27°                      | 27        | 15          | 46        | 31         | 6" x 4" x 72" DA    | 7" x 4" x 89.5" DA | 20'-24'             | 7,850          |
| EX60194S072R  | 60,000   | 194" | 206"         | 21' 5"  | 48°                       | 27°                      | 27        | 15          | 46        | 31         | 6" x 4" x 72" DA    | 7" x 4" x 89.5" DA | 20'-24'             | 7,850          |
| EX60194T121   | 60,000   | 194" | 206"         | 21' 5"  | 48°                       | 27°                      | 35        | 29          | 46        | 31         | 6"-5"-4" x 121" DAT | 7" x 4" x 89.5" DA | 20'-24'             | 8,075          |
| EX75194S072F7 | 75,000   | 194" | 206"         | 21' 5"  | 48°                       | 27°                      | 37        | 23          | 46        | 31         | 7" x 4" x 72" DA    | 7" x 4" x 89.5" DA | 20'-24'             | 7,850          |
| EX75194S072R7 | 75,000   | 194" | 206"         | 21' 5"  | 48°                       | 27°                      | 37        | 23          | 46        | 31         | 7" x 4" x 72" DA    | 7" x 4" x 89.5" DA | 20'-24'             | 7,850          |
| EX75194T121   | 75,000   | 194" | 206"         | 21' 5"  | 48°                       | 27°                      | 35        | 29          | 46        | 31         | 6"-5"-4" x 121" DAT | 7" x 4" x 89.5" DA | 20'-24'             | 8,075          |

\* Cycle Times are Factory developed and controlled by PTO output, oil viscosity, human and mechanical efficiency, and may vary accordingly.

CAUTION: This Equipment Should be Operated by Properly Trained Personnel. Improper Use, Misuse, or Lack of Maintenance Could Cause Injury to Persons or Property. Photos used in this brochure are illustrative only. We reserve the right to make changes at any time without notice. Information contained within this literature is believed to be the most accurate available at the time of printing.

