



TRANSPORT
PLATFORMS

SP SERIES



THE REFERENCE IN THE MARKET

The one-of-a-kind **SEP-5000** rack and pinion transport platform offers the highest load capacity of single-mast transport platforms. It does not require a concrete base and can be used both inside and outside a building. It distinguishes itself by the use of a flexible wall fastener and a system of adjustable tensioners.

All Fraco SEP Series transport platforms are designed for efficient movement of personnel and materials. They offer safety features both inside the cabin and at the landings to be serviced, thanks to an easy-to-use loading ramp. Their dimensions and capabilities can be customized to suit the needs of general and specialized contractors. They are manufactured with electrical and mechanical components that are available from local suppliers.

TECHNICAL DATA (SEP-5000)

	IMPERIAL	METRIC
STANDARD CAR LENGTH	12 FT 6 IN	3,8 M
MAXIMUM PAYLOAD	5 000 LB	2 270 KG
TRAVEL SPEED	0-39 FT / MIN	11,9 M / MIN
MAXIMUM HEIGHT	1 310 FT	400 M
STANDARD DISTANCE BETWEEN ANCHORS	30 FT	9 M
LIFTING SYSTEM	RACK AND PINION (MODULE 8)	
TYPE OF ENGINE (POWER SUPPLY)	ELECTRICAL MOTORS (3 PHASE 480V / 60HZ)	
INTERNAL CAR DIMENSIONS (L X W X H) / WEIGHT	12 FT 6 IN X 4 FT 9 IN X 7 FT 2 IN / 6 600 LB	3,8 M X 1,45 M X 2,1 M / 3 000 KG
MAST SECTION DIMENSIONS (L X W X H) / WEIGHT	26 IN X 26 IN X 5 FT / 341 LB	0,65 M X 0,65 M X 1,5 M / 155 KG
TYPE OF OPERATION	CONTROL PANEL WITH PUSH BUTTONS	
STANDARD COMPLIANCE	ANSI 92.10 - 2008; CSA B354.12-17	



CANADA

+ 1 800 267.0094
+ 1 450 658.0094

USA

+ 1 888 372.2648