

# INSPECTION FORM:

## Cable Lanyard



### OSHA 1926.502(d)(21)

Personal fall arrest systems SHALL be inspected prior to each use for wear, damage, and other deterioration, and defective components SHALL be removed from service.



### 6.1 Inspection

6.1.1 Equipment SHALL be inspected by the user before each use and, additionally, by a competent person other than the user at intervals of no more than one year.

LOOK AT:

1 HARDWARE

2 CABLE

3 WEBBING

4 STITCHING

5 LABELS/TAGS



PASS



FAIL

### Frequency of inspection in the following categories:

General Industry: \_\_\_\_\_ Construction: \_\_\_\_\_

Your Organization: \_\_\_\_\_ Manufacturer: \_\_\_\_\_

### Manufacturer of equipment:

Name of Manufacturer: \_\_\_\_\_

Serial #: \_\_\_\_\_ Model #: \_\_\_\_\_

Date of Manufacture: \_\_\_\_/\_\_\_\_/\_\_\_\_

### Inspection:

Date: \_\_\_\_/\_\_\_\_/\_\_\_\_

### Remove from service when:

Date: \_\_\_\_/\_\_\_\_/\_\_\_\_

### Name of competent person:

\_\_\_\_\_

### Name of user (authorized person):

\_\_\_\_\_



2	CABLE	<input checked="" type="checkbox"/>	<input type="checkbox"/>
---	-------	-------------------------------------	--------------------------

Rust/corrosion

Chemical damage

Birdcaging

Broken wire strands

Links/bent strands

3	WEBBING	<input checked="" type="checkbox"/>	<input type="checkbox"/>
---	---------	-------------------------------------	--------------------------

Cuts/burns/holes

Excessive wear

Excessive UV damage

Chemical attack

Other

4	STITCHING	<input checked="" type="checkbox"/>	<input type="checkbox"/>
---	-----------	-------------------------------------	--------------------------

Missing

Loose

Broken

Other

5	LABELS/TAGS	<input checked="" type="checkbox"/>	<input type="checkbox"/>
---	-------------	-------------------------------------	--------------------------

Missing

Illegible

Dates

Other

\*See user instruction manual for complete inspection procedures and requirements.