INSPECTION FORM:

Self-Retracting Lifeline



OSHA 1926.502(d)(21)

Personal fall arrest systems SHALL be inspected prior to each use for wear, damage, and other deterioration, and defective components SHALL be removed from service.



6.1 Inspection

6.1.1 Equipment SHALL be inspected by the user before each use and, additionally, by a competent person other than the user at intervals of no more than one year.

_	<i>c</i> •			e	•		•
Frequency	v at incr	NACTION	in the	こうけんしょ	wina	Cate	10riac:
i iequelic	y O1 1113 ₁		111 (115		vii iy	catet	101 I C 3.

Name of user (authorized person):				
Name of competent person:				
Date:/	Date:/			
Inspection:	Remove from service when:			
Date of Manufacture:/_	/			
Serial #:	Model #:			
Name of Manufacturer:				
Manufacturer of equip	ment:			
Your Organization:	Manufacturer:			
General Industry:	Construction:			



1 HARDWARE

2 WEBBING

3 STITCHING

4 LABELS/TAGS

1	HARDWARE	V	X
Rust/corrosion			
Deforn	ned/bent		
Burrs/e	cracks		
Weld spots/slag			
Missing rivets			
Springs			
Functionality			
Other			

2	WEBBING	$\overline{\mathbf{V}}$	X
Cuts/burns/holes			
Excessive wear			
Excessive UV damage			
Chemical attack			
Other			

3	STITCHING	\checkmark	X
Missing			
Loose			
Broker	1		
Other			

4	LABELS/TAGS	V	X
Missing			
Illegible			
Dates			
Other			







LOOK AT:

^{*}See user instruction manual for complete inspection procedures and requirements.