

**OSHA 1926.502(d)(21)**

Personal fall arrest systems SHALL be inspected prior to each use for wear, damage, and other deterioration, and defective components SHALL be removed from service.

**6.1 Inspection**

6.1.1 Equipment SHALL be inspected by the user before each use and, additionally, by a competent person other than the user at intervals of no more than one year.

**Frequency of inspection in the following categories:**

General Industry: \_\_\_\_\_ Construction: \_\_\_\_\_

Your Organization: \_\_\_\_\_ Manufacturer: \_\_\_\_\_

**Manufacturer of equipment:**

Name of Manufacturer: \_\_\_\_\_

Serial #: \_\_\_\_\_ Model #: \_\_\_\_\_

Date of Manufacture: \_\_\_\_/\_\_\_\_/\_\_\_\_

**Inspection:**

Date: \_\_\_\_/\_\_\_\_/\_\_\_\_

**Remove from service when:**

Date: \_\_\_\_/\_\_\_\_/\_\_\_\_

**Name of competent person:**

\_\_\_\_\_

**Name of user (authorized person):**

\_\_\_\_\_



LOOK AT: **1 HARDWARE**

**2 WEBBING**

**3 STITCHING**

**4 LABELS/TAGS**

☒ PASS ☐ FAIL

1	HARDWARE	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Rust/corrosion			
Deformed/bent			
Burrs/cracks			
Weld spots/slag			
Missing rivets			
Springs			
Functionality			
Other			

2	WEBBING	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Cuts/burns/holes			
Excessive wear			
Excessive UV damage			
Chemical attack			
Writing on the webbing			
Other			

3	STITCHING	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Missing			
Loose			
Broken			
Other			

4	LABELS/TAGS	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Missing			
Illegible			
Dates			
Other			

\*See user instruction manual for complete inspection procedures and requirements.