## **INSPECTION FORM:**

## Full Body Harness



## OSHA 1926.502(d)(21)

Personal fall arrest systems SHALL be inspected prior to each use for wear, damage, and other deterioration, and defective components SHALL be removed from service.



## 6.1 Inspection

6.1.1 Equipment SHALL be inspected by the user before each use and, additionally, by a competent person other than the user at intervals of no more than one year.

_	<i>c</i> •			e	•		•
Frequency	v at incr	NACTION	in the	こうけんしょ	wina	Cate	10riac:
i iequelic	y O1 1113 <sub>1</sub>		111 (115		vii iy	catet	101 I <del>C</del> 3.

General Industry:	Construction:		
Your Organization:	Manufacturer:		
Manufacturer of equipment			
Serial #:	Model #:		
Date of Manufacture://_			
Inspection:			
Date:/			
Name of competent persor	ո։		
Name of user (authorized person):			



LOOK AT: 1 HARDWARE 2 WEBBING

> 3 STITCHING 4 LABELS/TAGS

1	HARDWARE	$\overline{\checkmark}$	X
Rust/corrosion			
Deforn	ned/bent		
Burrs/cracks			
Weld spots/slag			
Missing rivets			
Springs			
Functionality			
Other			

2	WEBBING	$\overline{\checkmark}$	X
Cuts/burns/holes			
Excessive wear			
Excessive UV damage			
Chemical attack			
Other			

3	STITCHING	V	X
Missing			
Loose			
Broken			
Other			

4	LABELS/TAGS	$\checkmark$	X
Missing			
Illegible			
Dates			
Other			







<sup>\*</sup>See user instruction manual for complete inspection procedures and requirements.