

LARICK

6000 SERIES SANDER



The **LARICK 6000** Series machine will brush sand and/or wire brush parts with standard widths of 25, 37 and 49 inches. It has 2 to 6 spindles which will accommodate sanding or wire brushes up to 14 inch diameter and 50 inches long. It has a fixed height conveyor and accommodates parts up to 9 inches thick.

The spindles are belt driven with full power down to 450 RPM. Speed and direction are controlled from the touchscreen. Each motor's load is also displayed.

USER FRIENDLY MACHINERY
INNOVATIVE LEADER IN PROFILE SHAPING & SANDING



Outfeed End



Infeed End

Inverters control the feed rate, the spindles' speed, and rotational direction. Load meters aid setup and help maintain consistent results. Larger diameter sanding and wire brushes deliver best results.



Typical Sanding Brush



Typical Wire Brush



Adjusting Handle
with Digital Counter

As with all Larick Machines, it is designed with a small footprint, is rugged, dependable, and manufactured with as many 'off the shelf' parts as possible to minimize downtime and maintenance.

MACHINE SPECIFICATIONS

Spindle Motors: 2, 3, 5, 7.5 or 10HP

Voltage: 208-240V, 400-480V, or 575V 3ph

Variable Speed: AC Inverter, 200-900rpm

Spindles: 1.25" Dia.

Conveyor: 25, 37, 49 inch wide, 4-47 ft/min

Opening Height: Up to 9"

LARICK MACHINERY, INC.

409-A DELOZIER DR.

FORT COLLINS, CO 80524

PHONE 970-224-3061 FAX 970-224-9519

www.larickmachinery.com

info@larickmachinery.com