



Diamond 25™

DESCRIPTION

This Premium "Wet Look" Floor Finish is the central component of your floor care program. **Diamond25** is the simplest, most cost effective and versatile floor finish ever developed. Because of its unique polymer technology, this finish delivers a superior shine initially and offers improved durability over time, buffed at any speed. Our systems approach to floor maintenance includes this finish in conjunction with our **ReVital-eyes** floor finish laminator & maintainer and our new technology speed stripper, **Lightning Strip**. This system offers floor maintenance professionals great looking, long wearing floor surfaces with a simple, efficient, labor saving maintenance program.

PRODUCT FEATURES & ADVANTAGES

- **Durable:** High Solids for extended wear and superior protection for floor covering!
- **Easy to Use:** Self leveling, fast drying and excellent flow for easy application with little or no mop drag!
- **Appearance:** Fantastic deep gloss with crystal clarity and brighter floors, never yellows!
- **Resilient:** Black mark, dirt and detergent resistant with less coats for labor savings!

DIRECTIONS FOR USE

Strip and Re-coat: Using **Lightning Strip**, strip floor of old finish, paying extra attention to baseboards, corners, under shelving and fixtures, thresholds and built-up areas. Rinse thoroughly with clean water and allow to completely dry. Using a clean rayon mop or applicator, apply 4 coats of finish in thin uniform coats. Allow each coat to dry for a minimum of 25 minutes knowing humidity can effect dry time. Do not apply more than 4 coats in a 24 hour period. Allow floor to thoroughly dry before foot traffic is allowed in area.

Scrub and Re-coat: Sweep and dust mop entire floor. Dilute **TopScrub+** cleaner/maintainer, as directed, into the solution tank of the automatic scrubber. Scrub floor using a green scrubbing pad. Pick up all scrubbing solution and allow floor to dry completely. Using a clean rayon mop or applicator, apply 3 coats of finish in thin uniform coats. Allow each coat to dry for a minimum of 25 minutes knowing humidity can effect dry times. Allow floor to dry thoroughly before foot traffic is allowed in area.

Maintenance: **Diamond25** is an excellent finish for high speed burnishing of 1000 rpm or higher. Auto scrub or wet mop floor with **ReVital-eyes** neutral cleaner/maintainer, if wet mopping, rinse mop regularly. Allow floor to completely dry. Once dry, burnish floor with a high speed burnisher using a synthetic or natural hair buffing pad. For ultra-high speed propane burnishing use a white or tan burnishing pad.

Spray Buffing: Dilute **ReVital-eyes** as directed into a trigger sprayer. Working in small sections, spray solution directly on floor. Burnish floor with a high speed burnisher using a synthetic or natural burnishing pad or an ultra-high speed propane burnisher using a white or tan burnishing pad. Burnish floor to a high shine.

SPECIFICATIONS

Type	Pure acrylic polymers
Coverage (sq. ft / gal).....	2,500 - 3,000
pH.....	8.2 ± 0.3
Drying Time (minutes).....	30
% Styrene (Free Monomer)	0.0

Specific Gravity (g/cc)	1.03 ± 0.01
Color	White, opaque liquid
Odor.....	Typical acrylic
Powdering.....	None
Flash Point.....	None
Slip Resistant.....	Yes
Shelf Life	1 year minimum in original unopened container

SAFETY INFORMATION

KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash thoroughly after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is not known to be a "Hazardous Chemical" as

defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.gobeyondclean.com

KEEP FROM FREEZING

For Commercial and Industrial Use Only



FLOOR CARE

CLASSIFIED Floor Coating and Finishing Material
As to Slip Resistance Only
18EL



601 Heritage Drive, STE 422
Jupiter FL 33458
800-426-4246
www.GoBeyondClean.com