

HYDRA® RANDOM PACKING offers the most comprehensive designs and materials of random packing, and each engineered to create surface area for maximum vapor-to-liquid contact to optimize efficiency in chemical separation process of distillation, absorption and stripping.

雍原散堆填料®提供最全面的散堆填料設計和材料,各填料產品都經過精密設計,可創造最大的氣液接觸表面積,從而優化蒸餾、吸收和汽提等化學分離過程的效率。

Hydra International Co., Ltd.

2-F, No. 397, Section 4, Xin-Yi Road, Taipei, Taiwan 110

雍原有限公司

台北市信義路四段397號2樓

+886-2-2758-5298 info@hydra.com.tw www.hydra.com.tw



HYDRA® CERAMIC INTALOX SADDLES

| 雍原陶瓷馬鞍環 (矩鞍环)





Specification

Diameter (inch)	Diameter (mm)	Approx. Weight (km/m³)	Surface Area (m²/m³)	Free Volume (%)	Packing Factor (I/ft)
1/2"	12	770	623	71.7	200
3/4"	19	688	334	73	130
1"	25	620	253	73	85
1.5"	38	600	164	75	50
2"	50	577	115	77.4	37
3"	76	623	92	75.5	23

Note: Resistance to acids except in the case of hydrofluoric acid

The information herein does not constitute a guarantee or warranty. Hydra's Warranty is set forth in its standard terms and conditions which govern sales of Hydra's engineering services and engineered products. The standard terms are set forth in Hydra quotations and acknowledgements and are also available upon request.

