## **▲ CRESTO SAFETY**

## **RED PRO X BASIC**

## Rescue and evacuation device, bag

- · Extremely good lifting capacity
- Water sealed brake housing
- Intuitive and easy to use

Standards:

EN 341: 2011

EN 1496 : 2017

ANSI Z359.4-2013

CSA Z259.2.3-12



## **Product description**

The latest generation automatic evacuation and rescue device with superior properties.

RESQ RPX is the latest generation of rescue and evacuation equipment from RESQ – designed and developed for easy use with intuitive functions. The RPX can handle most rescue scenarios in various industries and extreme environments, from evacuation from high heights, lifting from deep shafts to advanced rescues, the height worker can feel confident that the equipment performance is verified.

The design and functionality of the device are based on insights from professionals working at heights daily. RPX is designed to give height workers verified confidence in extreme environments and for easy implementation of user-training and inspections.

Single-sided use for safe handling - all features on frontside - no more losing valuable time, twisting and turning the device to double-check. Universal power tool-interface for heavy lifting, up to 255m. Top-mounted swivel for optimal positioning, even in tight conditions and confined space. Laser printed, easy to read data and pictograms, engraved direct and permanently on the body. 280 kg – 255m verified and tested decent weight and height!

The device comes with a lifting function where the connection of machine-driven accessories simplifies and facilitates lifting at longer distances as standard. With the help of a power tool, the equipment can lift a load of 140 kg at a distance of 255 meters.

RPX requires a minimum of training which equals Low TCO for maintenance of training certificates for your workforce. Due to the easily recognizable and intuitive design on both rescue equipment and accessories, the kit is both practical and cost-efficient to introduce to already trained workforce which holds GWO or similar height training certificate.

RPX Basic is delivered as a complete set in a RESQ bag and accessory kit.

Material shortages due to the pandemic have resulted in the need for Cresto Group to periodically and temporarily replace certain components on our products with replacement components fulfilling the same function. Due to this, the product images may differ from that which is delivered.

| Product properties               |                                       |
|----------------------------------|---------------------------------------|
| Brand:                           | RESQ                                  |
| Material:                        | Polyamide, Aluminum , Techno polymers |
| Minimum load (kg):               | 40                                    |
| Maximum load (kg):               | 200                                   |
| Maximum number of users:         | 2                                     |
| Minimum working temperature (c): | -30                                   |
| Maximum working temperature (c): | 60                                    |

| EN-standard:                                     | EN 341 : 2011, EN 1496 : 2017   |          |        |               |                   |  |
|--|---|----------|--------|---------------|-------------------|--|
| Other standards:                                 | ANSI Z359.4-2013, CSA Z259.2.3-12   |          |        |               |                   |  |
| Notified body:                                   | 0200, FORCE Certification A/S, Main office, Park Allé 345, DK-2605 Brondby, Denmark |          |        |               |                   |  |
| Annual inspection:                               | Yes, every 12 months  |          |        |               |                   |  |
| Life span:                                       | 10 years  |          |        |               |                   |  |
| RFID:  | Yes   |          |        |               |                   |  |
| Warranty:  | 2 year  |          |        |               |                   |  |
| Declaration of Conformity:                       | Yes   |          |        |               |                   |  |
| Rope:  | Polyamide/polyamide 32-braided kernmantel construction 9,6mm                        |          |        |               |                   |  |
| Maximum rope length (m):                         | 255   |          |        |               |                   |  |
| Fall indicator:                                  | No  |          |        |               |                   |  |
| Maximum descent:                                 | 255 meters  |          |        |               |                   |  |
| Descent speed (m/s): 0,9-1,6                     |   |          |        |               |                   |  |
| Minimum breaking strength - MBS (kN):            | 20  |          |        |               |                   |  |
| Energy absorber:                                 | No  |          |        |               |                   |  |
| Gate feature:                                    | Tri-lock  | Tri-lock |        |               |                   |  |
| Gate strength (kN):                              | 16  |          |        |               |                   |  |
| Attaching connector 1:                           | Device: Aluminum carabiner with swivel  |          |        |               |                   |  |
| Attaching connector 2: Rope: Aluminum carabiner  |   |          |        |               |                   |  |
| Functions:                                       | Descend function, Lifting function  |          |        |               |                   |  |
| Extra functions:                                 | Lift with external power source   |          |        |               |                   |  |
| Mechanics:                                       | Centrifugal brake   |          |        |               |                   |  |
| Lifting mechanics:                               | Gear, ratio 1:9   |          |        |               |                   |  |
| Adjustable under load:                           | Yes   |          |        |               |                   |  |
| Reference Article name                           |   | Size (m) | Colors | GTIN          | Country of origin |  |
| 087003111025 RESQ, RPX200 Basic, 29              | 5m, bag, accs.  | 25       | BLACK  | 7350015799295 | Slovakia          |  |
| 087003111040 RESQ, RPX200 Basic, 40m, bag, accs. |   | 40       | BLACK  | 7350015799608 | Slovakia          |  |
| 087003111050 RESQ, RPX200 Basic, 50              | Om, bag, accs.  | 50       | BLACK  | 7350015799615 | Slovakia          |  |
| 087003111060 RESQ, RPX200 Basic, 60              | Om, bag, accs.  | 60       | BLACK  | 7350015799622 | Slovakia          |  |
|  |   |          |        |               |                   |  |

| 087003111075 | RESQ, RPX200 BASIC, 75M, BAG, ACCS.  | 75  | BLACK | 7350015799639 | Slovakia |
|--------------|--------------------------------------|-----|-------|---------------|----------|
| 087003111083 | RESQ, RPX200 Basic, 83m, bag, accs.  | 83  | BLACK | 7350015799646 | Slovakia |
| 087003111090 | RESQ, RPX200 Basic, 90m, bag, accs.  | 90  | BLACK | 7350015799653 | Slovakia |
| 087003111100 | RESQ, RPX200 Basic, 100m, bag, accs. | 100 | BLACK | 7350015799660 | Slovakia |
| 087003111105 | RESQ, RPX200 Basic, 105m, bag, accs. | 105 | BLACK | 7350015799677 | Slovakia |
| 087003111110 | RESQ, RPX200 Basic, 110m, bag, accs. | 110 | BLACK | 7350015799684 | Slovakia |
| 087003111120 | RESQ, RPX200 Basic, 120m, bag, accs. | 120 | BLACK | 7350015799691 | Slovakia |
| 087003111125 | RESQ, RPX200 Basic, 125m, bag, accs. | 125 | BLACK | 7350015799707 | Slovakia |
| 087003111150 | RESQ, RPX200 Basic, 150m, bag, accs. | 150 | BLACK | 7350015799714 | Slovakia |
| 087003111160 | RESQ, RPX200 Basic, 160m, bag, accs. | 160 | BLACK | 7350015790186 | Sweden   |