

eero PoE 6

- Dual-band Wi-Fi 6 Power over Ethernet (PoE) access point.
- Set up in minutes after installation. Easily mount on ceilings or walls with included bracket for maximum coverage.
- With eero for Pro Installers, you can set up, manage, view, and troubleshoot all your customers' networks in the eero app.



TOP PRODUCT BENEFITS



High-speed wifi

Supports wireless speeds up to 1.6 Gbps, to give you consistent streaming, gaming, and work from home experience in every part of your home or business.



Mountable, and power over ethernet enabled

802.3af (15W) Power-over-Ethernet (PoE) compatible with one auto-sensing 2.5 GbE port and one auto-sensing 1 GbE port. It can be easily mounted to walls or ceilings to maximize wifi coverage throughout your home.



Experience the eero TrueMesh difference

eero's TrueMesh networking technology helps optimize the wifi in your space for a seamless wifi experience.



Manage it all from the app

With eero for Pro Installers, you can set up, manage, view, and troubleshoot all your customers' networks in the eero app.



Gets better over time

Receive new features and updates automatically to keep improving your network's performance and security.



Free support when you need it

If you have questions during the setup process or encounter a technical issue, our expert wifi troubleshooters are ready to help by phone in the US at 1-877-659-2347 or by email at support@eero.com

SKU

T011111

PACKAGING INCLUDES

One eero PoE 6, mounting bracket, mounting accessories

TECHNICAL SPECIFICATIONS

Wireless and RF

Wi-Fi 6 (IEEE 802.11a/b/g/n/ac/ax)
Dual-Band (2.4 GHz, 5 GHz)
20, 40, 80, 160 MHz Channel Widths
Automatic Channel Selection, Band Steering
WPA2-AES, WPA3-Personal Transition Mode
2x2/2x2 MU/SU-MIMO, 4 Spatial Streams
WMM, Tx Beamforming, OFDMA
AX3000 Rating (2.4 GHz: 574 Mbps, 5 GHz:
2402 Mbps)

Operating Frequencies

ISM (2.4–2.484 GHz)
U-NII-1 (5.15–5.25 GHz)
U-NII-2A (5.25–5.35 GHz, DFS)
U-NII-2C (5.47–5.725 GHz, DFS)
U-NII-3 (5.725–5.85 GHz)
U-NII-4 (5.850–5.925 GHz)

Wired and Power over Ethernet

One auto-sensing 2.5 gigabit, PoE capable
Ethernet port
One auto-sensing gigabit Ethernet port
802.3bt 4 pair Class 3 (802.3bt or 802.3af)

Smart Home, Certifications, and Parental Controls

Alexa Smart Home Hub
Bluetooth Low Energy, Zigbee, Thread
Works with Alexa
Certified for Humans
Device & Profile Pausing
Guest Network

Management Tool and Additional Services

eero iOS & Android mobile applications
eero Plus*
eero for Professional Installers*
eero for Business*
eero for Service Providers*

Warranty and Support

1-year limited warranty
Contact 1-877-659-2347 or
support.eero.com

Additional Specifications

Compute

1 GHz dual-core processor, 512MB RAM,
4GB Flash

Dimensions

6.45 x 6.45 x 1.7 inches
(163.8 x 163.8 x 43mm)
*Actual size may vary by manufacturing
process.*

Weight

1.04 lbs (473g)

Operating Temperature

32° to 104°F (0° to 40°C)

Electrical Requirements

100–240V AC, 50/60Hz or PoE (802.3af)

Power

Compatible with PoE (802.3af) or 15W
eero power supply