

GULF FIRE®

FIRE EXTINGUISHERS



KM 553375



GULF FIRE FIGHTING EQUIPMENTS FZE





P.O.Box 262329 Jebel Ali Free Zone, Dubai , United Arab Emirates

Tel: +971 4880 7127 - Fax: +971 4880 7604

Email: gulffirefze@yahoo.com www.gulffire.com





Model				
GFP1	8 A	34 B	●	●
GFP2	13 A	70 B	●	●
GFP4	21 A	113 B	●	●
GFP6	34 A	183 B	●	●
GFP9	43 A	233 B	●	●
GFP12	55 A	233 B	●	●



The **GULF FIRE®** Dry Powder Fire Extinguishers are manufactured according to the Specifications of **BS EN 3** Part 7, 8, 10 Standard and got certified by **BSI** for **KITEMARK**. The cylinder itself complies with 97/23/EC (PED). It is very efficient in Knocking out the fire and each model has achieved the best Fire rating. All Models comes with wall mounting bracket and models from 4 Kg have strong plastic base.

ABC DRY POWDER EXTINGUISHER						
MODEL	GFP1	GFP2	GFP4	GFP6	GFP9	GFP12
CAPACITY	1 KG	2 KG	4 KG	6 KG	9 KG	12 KG
FIRE RATINGS	8A / 34B	13A / 70B	21A / 113B	34A / 183B	43A / 233B	55A / 233B
DISCHARGE TIME (sec)	6	11	13	17	29	34
DISCHARGE RANGE, APPROX	4 -5 m	4 -5 m	6 -7 m	6 -7 m	6 - 8 m	6 - 8 m
DIMENSION (H X D)mm	333 x 85	400 x 110	492 x 135	512 x 162	585 x 182	736 x 182
EXTINGUISHANT	ABC 40% DRY CHEMICAL POWDER					
PROPELLANT	NITROGEN					
TYPE	STORED PRESSURE					
CLASS OF FIRE	A, B, C & ELECTRICAL FIRES					
CYLINDER BODY	COLD ROLL STEEL SHEET					
OPERATING VALVE	BRASS					
TEST PRESSURE	27 BAR					
WORKING PRESSURE	14 BAR					
WORKING TEMPERATURE	-20° C TO + 60° C					





TECHNICAL SPECIFICATION:

- Multipurpose Application
- Body Made of Cold Rolled Mild Steel sheet
- Easy Squeeze grip operation
- Controlled Discharge
- High Quality Powder coating with Polyester finish
- Suitable for A, B, C classes of Fires. Safe to use on electrical fires
- Easy to operate as well as to recharge

APPLICATION:

- Warehouse
- Industries
- Commercial Building
- Residential Buildings
- Schools
- Offices
- Automobiles



Model				
GFW6	13 A			
GFW9	21 A			
GFF6	13 A	144 B		
GFF9	21 A	183 B		



KM 553375



0036

The **GULF FIRE®** Water based Portable Fire Extinguishers are manufactured & Tested according to the Specifications of **BS EN 3** Part 7, 8,10 & got certified by **BSI** for **KITEMARK**. The cylinder itself complies with 97/23/EC (PED). All Models comes with wall mounting bracket as well as strong plastic base.

WATER BASED FIRE EXTINGUISHER				
MODEL	GFW6	GFW9	GFF6	GFF9
CAPACITY	6 L	9 L	6 L	9 L
FIRE RATINGS	13A	21A	13A/144B	21A/183B
DISCHARGE TIME (sec)	29	35	21	34
DISCHARGE RANGE, APPROX	5 m	6 m	5 m	6 m
DIMENSION (H X D)mm	512 X 162	585 X 182	512 X 162	585 X 182
EXTINGUISHANT	WATER		3% AFFF FOAM	
PROPELLANT	NITROGEN			
TYPE	STORED PRESSURE			
CLASS OF FIRE	A		A , B	
CYLINDER BODY	COLD ROLL STEEL SHEET			
OPERATING VALVE	BRASS			
TEST PRESSURE	27 BAR			
WORKING PRESSURE	14 BAR			
WORKING TEMPERATURE	+5° C TO +60° C			

FEATURES:

- Body Made of Cold Rolled Mild Steel sheet
- High Quality Powder coating with Polyester finish
- Polyethylene Internal Lining prevent it from corrosion
- Easy to Operate and also to recharge
- Suitable for fires involving Live electrical equipment

APPLICATION:





WATER GAS FIRE EXTINGUISHERS:

Schools, Industries, Warehouse residential buildings etc.

FOAM FIRE EXTINGUISHERS:

Refineries, Oil Storage, Power Plants Paint storage etc.



Model				
GFC2		34 B		•
GFC5		55B		•

The **GULF FIRE®** CO₂ Portable Fire Extinguishers are manufactured & Tested according to the Specifications of **BS EN 3** Part 7, 9 & 10 Standard. It also got certified by **BSI** for **KITEMARK**. Carbon dioxide is a colourless, odourless, non toxic gas which acts as a clean agent while fighting against fire. This specific character made it the best to put off fires in offices which involve computers or other Electronic equipments.

CO2 FIRE EXTINGUISHER		
MODEL	GFC2	GFC5
CAPACITY	2 KG	5 KG
FIRE RATINGS	34B	55B
DISCHARGE TIME (sec)	9	15
DISCHARGE RANGE, APPROX	4-5 m	5-6 m
DIMENSION (H X D)mm	575 x 103	750 x 136
EXTINGUISHANT	CARBON DIOXIDE	
CLASS OF FIRE	B & ELECTRICAL FIRES	
CYLINDER BODY	CARBON STEEL (34CrMo4)	
OPERATING VALVE	BRASS	
TEST PRESSURE	250 BAR	
WORKING PRESSURE	60 BAR	
WORKING TEMPERATURE	-20° C TO +60° C	

FEATURES:

- Controlled Discharge
- Body Made of Carbon Molybdenum Steel (Seamless)
- High Quality Powder coating with Polyester finish which fight against corrosion
- Suitable for Fires due to Oil, Gas. Safe to use on electrical fires
- Comes with Wall Mounting Bracket
- Easy to Recharge

APPLICATION:

- Offices
- Restaurants
- Commercial Building
- Residential Buildings
- Laboratories
- Warehouse